

CP- UNC-TB20ZL6-MD**2 MP Full HD IR Bullet Camera - 60Mtr.****Main Features**

- 1/2.7" 2MP PS CMOS Image Sensor
- Max 25fps@1080P
- H.264 and MJPEG dual-stream encoding
- WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC
- 2.7~12mm motorized lens
- IR Range of 60 Mtrs, IP67, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP- UNC-TB20ZL6-MD

2 MP Full HD IR Bullet Camera - 60Mtr.



Feature

Image Sensor
Minimum Illumination
Shutter Speed
White Balance
Gain Control(AGC)
Lens
Back Light Compensation
S/N Ratio
Video Compression
Video Streaming
Resolution
Privacy Mask
ICR

Specification

1/2.7" 2MP Progressive scan CMOS
0. 1Lux/F1.4 (Color), 0Lux/F1.4(IR on)
Auto/Manual, 1/3(4)~1/10000s
Auto/Manual
Auto/Manual
2.7mm~12mm motorized Lens
BLC/ HLC/ WDR(120dB)
More than 50dB
H.264/ H.264H/ MJPEG
Main Stream: 1080P/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
1080P(1920x1080) / 1.3M(1280x960) / 720P(1280x720) / D1(704x576/704x480) /CIF
Up to 4 areas
Auto(ICR)/Color/B/W

Protocol
IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS,Bonjour, ONVIF, PSIA, CGI

Ethernet
RJ-45 (10/100Base-T)

User Account
20 Users

Smart Phone
iPhone, iPad, Android, Windows Phone

IR
IR Range of 60 Mtr.

Micro SD
Micro SD, Max 128GB

Operating Temperature
-30°C~+60°C , Less than 95%RH

Power Source
DC12V, PoE (802.3af)

Power Consumption
Max 13W

Weatherproof Standard
IP67

Dimension
72mm× 80mm× 212.8mm

Weight
0.65kg