




Comparison Table of GV-3D People Counter and GV-3D People Counter V2

	GV-3D People Counter	GV-3D People Counter V2
Device Front View		
Mechanical		
Video Output	HDMI / VGA	N/A
IR Remote Control	Yes	N/A
Power	12V / 3A DC Jack	PoE Only
Ethernet	10/100 Ethernet	10/100 Ethernet
Audio	3.5mm Jack (for alarm)	N/A
Digital I/O	N/A	8-pin terminal block (DC 5V, 5 mA)
Local Storage	SDHC card slot (SD/SDHC, Class 4 or above, FAT32 format)	Micro SD card slot (SD/SDHC/SDXC/UHS-I, Class 10 or above)
Interfaces	USB 2.0 (For Asus Xtion pro or GV-GPS Receiver)	1 Sensor Input (DC 5V, 5 mA) 1 Alarm Output (DC 5V, 5 mA) UART (For GV-GPS Receiver)
General Information		
Weather Resistance	Indoor only	
Operating Temperature	0 °C ~ 40 °C (32 °F ~ 104 °F)	
Operating Humidity	20 % ~ 80 % (with no condensation)	
Operating Distance	0.6 ~ 5 m (1.97 ~ 16.40 ft.)	1.8 ~ 4 m (5.91 ~ 13.12 ft.)
Regulatory	CE, FCC compliant	CE, FCC, RCM compliant
Dimension (W x H x D)	182.3 x 28.9 x 131 mm (7.18 x 1.14 x 5.16 in)	150 x 48.5 x 37.5mm (5.9 x 1.9 x 1.47 in)
Net Weight	615 g (1.36 lb)	200 g (0.44 lb)
Supported Browser	Mozilla Firefox, Google Chrome	Microsoft Internet Explorer V10.0 or above
Language (Web Interface)	English, Traditional Chinese, Simplified Chinese	English, Traditional Chinese, Simplified Chinese, Russian, French