

CP- VNC-T20FR3-M**2 MP HD VF IR Array Bullet Camera - 30Mtr.****INDIGO****Main Features**

- 1/2.8" 2MP PS CMOS Image Sensor
- Max 25fps@2MP
- H.264 and MJPEG Triple-stream encoding
- DWDR, Day/Night(ICR), 2D/3D-DNR, AWB, AGC, BLC
- 2.8~12mm Varifocal Lens
- IR Range of 30 Mtrs, Micro SD, IP66, PoE
- Mobile Software for Android, iOS
- CMS Software: IVMS



CP- VNC-T20FR3-M

2 MP HD VF IR Array Bullet Camera - 30Mtr.



Feature

Image Sensor
 Minimum Illumination
 Shutter Speed
 White Balance
 Lens
 Gain Control(AGC)
 Video Compression
 S/N Ratio
 Video Streaming
 Resolution
 Frame Rate
 Privacy Mask
 ICR
 Audio Input
 Audio Output
 Audio Compression
 Alarm IN
 Alarm Out
 WDR
 Protocol
 Ethernet
 IR
 OSD
 Micro SD
 Operating Temperature
 Humidity
 Power Source
 Power Consumption
 Weatherproof Standard
 Dimension
 Weight

Specification

1/2.8" 2MP Progressive scan CMOS
 Colour: 0.06 Lux (F1.4, 50IRE), Black & White: 0.03Lux (F1.4, 50IRE)
 Auto/Manual, 1/6~1/8000 s
 Auto/Manual
 2.8~12mm Varifocal Lens
 Auto/Manual
 H.264/MJPEG
 >52dB
 Triple
 1.3MP @ 25fps
 1.3MP(1280x960)/720P(1280x720)/D1720x576) @ 25 fps
 Up to 4 areas
 IR-cut filter with auto switch (ICR)
 impedance 35 kΩ; amplitude 2 V [p-p]
 impedance 600 Ω; amplitude 2 V [p-p]
 G.711
 1 IN
 1 Out
 Digital
 L2TP,IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP,PPPoE,RTP,RTSP,Qos,NTP,FTP,HTTP,SNMP,SIP,
 10M/100M Base-TX Ethernet
 IR Range of 30 Mtr.
 Up to 8 OSDs
 Up to 64 GB
 -35°C ~ +60°C (-31°F ~ 140°F)
 ≤ 90% RH(non-condensing)
 12 V DC, or PoE (IEEE802.3 af)
 3.5W (5.5W with IR on)
 IP66
 253.4 × 86 × 71.7 mm (9.98" × 3.4" × 2.8")
 0.93 kg