

CP- VNC-T20FR3-MD**2 MP WDR VF IR Array Bullet Camera - 30Mtr.****INDIGO****Main Features**

- 1/2.8" 2MP PS CMOS Image Sensor
- Max 25fps@2MP
- H.264 and MJPEG Triple-stream encoding
- WDR, Day/Night(ICR), 2D/3D-DNR, AWB, AGC, BLC
- 3 ~ 10.5 mm Varifocal Lens
- IR Range of 30 Mtrs, Micro SD, IP66, PoE
- Mobile Software for Android, iOS
- CMS Software: IVMS



CP- VNC-T20FR3-MD

2 MP WDR VF IR Array Bullet Camera - 30Mtr.



Feature

Image Sensor
 Minimum Illumination
 Shutter Speed
 White Balance
 Lens
 Gain Control(AGC)
 S/N Ratio
 Video Compression
 Video Streaming
 Resolution
 Frame Rate
 Privacy Mask
 ICR
 Audio Input
 Audio Output
 Audio Compression
 Alarm IN
 Alarm Out
 WDR
 Interface
 Protocol
 Ethernet
 OSD
 IR
 Micro SD
 Operating Temperature
 Humidity
 Power Source
 Power Consumption
 Weatherproof Standard
 Dimension
 Weight

Specification

1/2.8" 2MP Progressive scan CMOS
 Colour: 0.02 Lux (F1.4, 50IRE), Black & White: 0.08Lux (F1.4, 50IRE)
 Auto/Manual, 1/6~1/8000 s
 Auto/Manual
 3~10.5mm Varifocal Lens
 Auto/Manual
 >52dB
 H.264/MJPEG
 Triple
 1080P @ 25fps
 1080P(1920x1080)/720P(1280x720)/D1720x576) @ 25 fps
 Up to 4 areas
 IR-cut filter with auto switch (ICR)
 impedance 35 k Ω ; amplitude 2 V [p-p]
 impedance 600 Ω ; amplitude 2 V [p-p]
 G.711
 2 IN
 1 Out
 Upto 120 dB
 1 RS485
 L2TP,IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP,PPPoE,RTP,RTSP,Qos,NTP,FTP,HTTP,SNMP,SIP,
 10M/100M Base-TX Ethernet
 Up to 8 OSDs
 IR Range of 30 Mtr.
 Up to 64 GB
 -40°C ~ +60°C (-40°F ~ 140°F)
 \leq 90% RH(non-condensing)
 12 V DC, 24 V AC or PoE (IEEE802.3 af)
 4.5 W (11W with IR on)
 IP66
 282.6 x90 x86 mm (11.1" x 3.5" x 3.4")
 1.2 kg

 **CP- VNC-T20FR3-MD**

2 MP WDR VF IR Array Bullet Camera - 30Mtr.



Feature

Specification