



Contents


Box Camera Specifications (Part 1)	3
Box Camera Specifications (Part 2)	4
Box Camera Specifications (Part 3)	5
Box Camera Specifications (Part 3)	6
Ultra Box Camera Specifications	7
IR Arctic Box Camera Specifications (Part 1)	8
IR Arctic Box Camera Specifications (Part 2)	9
IR Arctic Box Camera Specifications (Part 3)	10
Bullet Camera Specifications (Part 1)	11
Bullet Camera Specifications (Part 2)	12
Bullet Camera Specifications (Part 3)	13
Ultra Bullet Camera Specifications (Part 1)	14
Ultra Bullet Camera Specifications (Part 2)	15
Vandal Proof Dome Specifications (Part 1)	16
Vandal Proof Dome Specifications (Part 2)	17
Vandal Proof Dome Specifications (Part 3)	18
Vandal Proof Dome Specifications (Part 4)	19
Fixed Dome Specifications (Part 1)	20
Fixed Dome Specifications (Part 2)	21
Fixed Dome Specifications (Part 3)	22
Cube Camera Specifications	23
Advanced Cube Camera Specifications	24
Mini Fixed Dome Specifications (Part 1)	25



Mini Fixed Dome Specifications (Part 2).....	26
Mini Fixed Rugged Dome Specifications (Part 1).....	27
Mini Fixed Rugged Dome Specifications (Part 2).....	28
Target Series Specifications (Part 1).....	29
Target Series Specifications (Part 2).....	30
PT and PTZ Camera Specifications.....	31
Fisheye Camera Specifications (Part 1)	32
Fisheye Camera Specifications (Part 2)	33
Fisheye Camera Specifications (Part 3)	34
Fisheye Camera Specifications (Part 4)	35
Fisheye Camera Specifications (Part 5)	36
Fisheye Camera Specifications (Part 6)	37
IP Speed Dome Camera Specifications (Part 1)	38
IP Speed Dome Camera Specifications (Part 2)	39
IP Speed Dome Camera Specifications (Part 3)	40
Pinhole Camera Specifications	41



Box Camera Specifications (Part 1)








	GV-BX120D Varifocal Lens	GV-BX140DW Varifocal Lens	GV-BX130D Series Fixed Lens	GV-BX130D Series Varifocal Lens	GV-BX220D Series Varifocal Lens	GV-BX320D Series Varifocal Lens	GV-BX520D Varifocal Lens	
								
Camera								
Image Sensor	1/3" progressive scan low lux CMOS	1/3" progressive scan CMOS	1/2.5" progressive scan CMOS					
Picture Elements	1280 (H) x 1024 (V)	1280 (H) x 720 (V)	1280 (H) x 1024 (V)	1920 (H) x 1080 (V)	2048 (H) x 1536 (V)	2560 (H) x 1920 (V)		
Minimum Illumination	Color	0.05 Lux	0.2 Lux	0.15 Lux				
	B/W	0.03 Lux	0.08 Lux	0.10 Lux				
	IR ON	0 Lux						
Shutter Speed	Auto, Manual (1/5 ~ 1/4000 sec)	Auto	Auto, Manual (1/5 ~ 1/8000 sec)					
White Balance	Auto, Manual (2800K ~ 8500K)							
Gain Control	Automatic							
S/N Ratio	50 dB	47 dB	45 dB					
WDR Pro (with WDR sensor)	N/A	Yes	N/A					
Dynamic Range	Up to 72 dB	Up to 100 dB	Up to 72 dB					
Operation								
Video Compression	H.264, MJPEG							
Video Streaming	Dual streams							
Frame Rate	30 fps at 1280 x 1024	30 fps at 1280 x 720	30 fps at 1280 x 1024	30 fps at 1920 x 1080	20 fps at 2048 x 1536	10 fps at 2560 x 1920		
Audio Compression	G.711, AAC (optional)							
Sensor Input	1 input (Dry Contact)							
Alarm Output	1 Digital Output (200mA 5V DC)							
Optical Lens								
Megapixel	Yes							
Day/Night	Yes (with removable IR-cut filter)							
Lens Type	Varifocal Lens	Fixed Lens	Varifocal Lens					
Focal Length	2.8 ~ 12 mm	4.0 mm	2.8 ~ 12 mm	GV-BX220D-2 2.8 ~ 6 mm GV-BX220D-3 2.8 ~ 12 mm	GV-BX320D-0 3.1 ~ 8 mm GV-BX320D-1 2.8 ~ 6 mm	4.5 ~ 10 mm		
Maximum Aperture	F/1.4	F/1.5	F/1.4	GV-BX220D-2 F/1.3 GV-BX220D-3 F/1.4	GV-BX320D-0 F/1.2 GV-BX320D-1 F/1.3	F/1.6		
Mount	CS Mount							
Image Format	1/3"						1/2"	
Operation	Focus	Manual (w/lock)						
	Zoom	Manual (w/lock)	Fixed	Manual (w/lock)				
	Iris	DC drive	Fixed	Fixed	DC drive			Manual(w/lock)
Mechanical								
Temperature Detector	Yes							
Connectors	Power	2-pin terminal block, PoE						
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector						
	Audio	1 In (built-in or external microphone), 1 Out (Stereo phone jack, 3.5 mm / 0.14")						
	Digital I/O	3-pin terminal block, pitch 2.5 mm / 0.1"						
	Auto Iris	DC drive	Not functional	DC drive				Not functional
	Local Storage*	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported						
LED Indicator	BNC connector (640 x 480 resolution) 2 LEDs: Power, Status							
General								
Environment Temperature	0 °C ~ 50 °C (32 °F ~ 122 °F)							
Humidity	10% to 90% (no condensation)							
Power Source	12V DC / PoE (IEEE 802.3af)							
Max. Power Consumption	7 W							
Regulatory	CE, FCC, RCM, RoHS compliant							
Dimensions (L X W X H) (Without lens)	75.5 x 75 x 54 mm (2.97" x 2.95" x 2.13")							
Weight	321 g (0.71 lb)							

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- The TV-Out function only works in 640 x 480 resolution. For TV-Out to work properly, you must set the video resolution to 1280 x 1024 or lower. If both streams are enabled, the Sub Stream must be set to 640 x 480.
- Memory card slot (local storage) is not supported in Argentina.



Box Camera Specifications (Part 2)










	GV-BX1300 Series		GV-BX2400 Series				GV-BX3400 Series						
	GV-BX1300-0F ~2F	GV-BX1300-3V	GV-BX2400-1F ~2F	GV-BX2400-3V~4V	GV-BX3400-1F ~2F GV-BX3400-8F	GV-BX3400-4V~5V	GV-BX3400-3V P-Iris (Coming)						
	Fixed Lens	Varifocal Lens	Fixed Lens	Varifocal Lens	Fixed Lens	Varifocal Lens	Varifocal Lens	Varifocal Lens					
													
Camera													
Image Sensor	1/2.5" progressive scan CMOS				1/3.2" progressive scan CMOS								
Picture Elements	1280 (H) x 1024 (V)		1920 (H) x 1080 (V)			2048 (H) x 1536 (V)							
Minimum Illumination	Color	0.15 Lux		0.08 Lux									
	B/W	0.10 Lux		0.05 Lux									
	IR ON	0 Lux											
Shutter Speed	Auto, Manual (1/5 ~ 1/8000 sec)												
White Balance	Auto, Manual (2800K ~ 8500K)												
Gain Control	Automatic												
S/N Ratio	45 dB		47 dB										
WDR Pro (with WDR Sensor)	N/A		Yes										
Dynamic Range	Up to 72 dB		Up to 100 dB										
Operation													
Video Compression	H.264, MJPEG												
Video Streaming	Dual streams												
Frame Rate	30 fps at 1280 x 1024		30 fps at 1920 x 1080			20 fps at 2048 x 1536 30 fps at 1920 x 1080							
Audio Compression	G.711, AAC (optional)												
Sensor Input	1 input (Dry Contact)												
Alarm Output	1 Digital Output (200mA 5V DC)												
Optical Lens													
Megapixel	Yes												
Day/Night	Yes (with removable IR-cut filter)												
Lens Type	Fixed Lens		Varifocal Lens		Fixed Lens		Varifocal Lens						
Focal Length	BX1300-0F	4 mm	2.8 ~ 12 mm	BX2400-1F	8 mm	BX2400-3V	2.8 ~ 12 mm	BX3400-1F	8 mm	BX3400-4V	3 ~ 10.5 mm	BX3400-3V	3 ~ 10.5 mm
	BX1300-1F	8 mm		BX2400-2F	12 mm	BX2400-4V	3 ~ 10.5 mm	BX3400-2F	12 mm	BX3400-5V	2.8 ~ 6 mm		
	BX1300-2F	12 mm				BX3400-8F	2.8 mm						
Maximum Aperture	BX1300-0F	F/1.5	F/1.4	BX2400-1F	F/1.6	BX2400-3V	F/1.4	BX3400-1F	F/1.6	BX3400-4V	F/1.4	F/1.4	F/1.4
	BX1300-1F	F/1.6		BX2400-2F	F/1.6	BX2400-4V	F/1.4	BX3400-2F	F/1.6	BX3400-5V	F/1.3		
	BX1300-2F	F/1.6				BX3400-8F	F/1.8						
Mount	CS Mount												
Image Format	BX1300-0F	1/3"	1/2.7"	BX2400-1F	1/2.5"	BX2400-3V	1/2.7"	BX3400-1F	1/2.5"	BX3400-4V	1/2.7"	1/2.7"	1/2.7"
	BX1300-1F	1/2.5"		BX2400-2F	1/2.5"	BX2400-4V	1/2.7"	BX3400-2F	1/2.5"	BX3400-5V	1/3"		
	BX1300-2F	1/2.5"						BX3400-8F	1/2.5"				
Horizontal FOV	BX1300-0F	49°	64° ~ 23°	BX2400-1F	32°	BX2400-3V	77° ~ 28°	BX3400-1F	35°	BX3400-4V	78° ~ 28°	BX3400-3V	78° ~ 28°
	BX1300-1F	26°		BX2400-2F	21°	BX2400-4V	73° ~ 27°	BX3400-2F	23°	BX3400-5V	94° ~ 45°		
	BX1300-2F	17°						BX3400-8F	88°				
Operation	Focus	Manual w/lock											
	Zoom	Fixed	Manual (w/lock)	Fixed	Manual (w/lock)	Fixed	Manual (w/lock)	Fixed	Manual (w/lock)	Fixed	Manual (w/lock)	Fixed	Manual (w/lock)
	Iris	Fixed	DC drive	Fixed	DC drive	Fixed	DC drive	Fixed	DC drive	Fixed	DC drive	Fixed	P-Iris
Mechanical													
Temperature Detector	Yes												
Connectors	Power	2-pin terminal block, PoE											
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector											
	Audio	1 In (built-in or external microphone), 1 Out (Stereo phone jack, 3.5 mm / 0.14")											
	Digital I/O	3-pin terminal block, pitch 2.5 mm / 0.1"											
	Auto Iris	Not functional	Yes	Not functional	Yes	Not functional	Yes	Not functional	Yes	Not functional	Yes	Not functional	Yes
	Local Storage*	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported											
	TV-Out	BNC connector (640 x 480 resolution)											
Mini USB	GV-WiFi Adapter or USB hard drive												
LED Indicator	2 LEDs: Power, Status												
General													
Environment Temperature	0 °C ~ 50 °C (32 °F ~ 122 °F)												
Humidity	10% to 90% (no condensation)												
Power Source	12V DC / PoE (IEEE 802.3af Class 3)												
Max. Power Consumption	9.5 W				9.5 W				7.12 W				
Regulatory	CE, FCC, RCM, RoHS compliant												
Dimensions (L X W X H)	75.5 x 75 x 54 mm (2.97" x 2.95" x 2.13") without lens												
Weight	300 g (0.66 lb)												

- Note:**
- Product design and specifications are subject to change without notice.
 - The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
 - The TV-Out function only works under 640 x 480 resolution. For TV-Out to work properly, set the video resolution to 1280 x 1024 or lower. If both streams are enabled, the Sub Stream must be set to 640 x 480.
 - Memory card slot (local storage) is not supported in Argentina.

- Mind the following limitations and requirements for the mini USB port:
 - The USB hard drive must be of 2.5" or 3.5", version 2.0 or above
 - The USB hard drive's storage capacity must not exceed 2TB
 - USB flash drives and USB hubs are not supported
 - External power supply is required for the USB hard drive
 - To connect a GV-WiFi Adapter, make sure it is connected before the camera is powered on.




Box Camera Specifications (Part 3)

	GV-BX1500 Series					GV-BX2500 Series			GV-BX5300 Series					
	GV-BX1500-1F ~ 2F GV-BX1500-8F		GV-BX1500-3V	GV-BX1500-3V P-Iris (Coming)		GV-BX2500-1F ~ 2F GV-BX2500-8F		GV-BX2500-3V	GV-BX2500-3V P-Iris (Coming)		GV-BX5300-8F	GV-BX5300-6V	GV-BX5300-6V P-Iris (Coming)	
	Fixed Lens		Varifocal Lens	Varifocal Lens		Fixed Lens		Varifocal Lens	Varifocal Lens		Fixed Lens	Varifocal Lens	Varifocal Lens	
														
Camera														
Image Sensor	1/3" progressive scan super low lux CMOS					1/2.8" progressive scan super low lux CMOS			1/2.5" progressive scan CMOS					
Picture Elements	1280 (H) x 1024 (V)					1920 (H) x 1080 (V)			2560 (H) x 1920 (V)					
Minimum Illumination	Color		0.01 Lux			0.02 Lux		0.15 Lux						
	B/W		0.01 Lux			0.02 Lux		0.10 Lux						
	IR ON		0 Lux											
Shutter Speed	Auto, Manual (1/5 ~ 1/8000 sec)													
White Balance	Auto, Manual (2800K ~ 8500K)													
Gain Control	Automatic													
S/N Ratio	55 dB					52 dB			45 dB					
WDR Pro (with WDR Sensor)	N/A					N/A			N/A					
Dynamic Range	Up to 72 dB													
Operation														
Video Compression	H.264, MJPEG													
Video Streaming	Dual streams													
Frame Rate	30 fps at 1280 x 1024					30 fps at 1920 x 1080			10 fps at 2560 x 1920					
Audio Compression	G.711, AAC (optional)													
Sensor Input	1 input (Dry Contact)													
Alarm Output	1 Digital Output (200mA 5V DC)													
Optical Lens														
Megapixel	Yes													
Day/Night	Yes (with removable IR-cut filter)													
Lens Type	Fixed		Varifocal Lens			Fixed		Varifocal Lens		Fixed		Varifocal Lens		
Focal Length	BX1500-1F	8 mm	2.8 ~ 12 mm	BX1500-3V	3 ~ 10.5 mm	BX2500-1F	8 mm	2.8 ~ 12 mm	BX2500-3V	3 ~ 10.5 mm	2.8 mm	4.5 ~ 10 mm	3.3 ~ 10.5 mm	
	BX1500-2F	12 mm				BX2500-2F	12 mm							
	BX1500-8F	2.8 mm				BX2500-8F	2.8 mm							
Maximum Aperture	BX1500-1F	F/1.6	F/1.4		F/1.4	BX2500-1F	F/1.6	F/1.4		F/1.4	F/1.8	F/1.6	F/1.4	
	BX1500-2F	F/1.6				BX2500-2F	F/1.6							
	BX1500-8F	F/1.8				BX2500-8F	F/1.8							
Mount	CS Mount													
Image Format	BX1500-1F		1/2.5"		1/2.7"	BX2500-1F		1/2.5"	1/2.7"		1/2.7"	1/2.5"	1/2"	1/2.5"
	BX1500-2F	1/2.5"				BX2500-2F	1/2.5"							
	BX1500-8F					BX2500-8F								
Horizontal FOV	BX1500-1F	36°	86° ~ 31°	BX1500-3V	81° ~ 29°	BX2500-1F	40°	105° ~ 36°	BX2500-3V	96° ~ 34°	112°	70° ~ 34°	84° ~ 35°	
	BX1500-2F	23°				BX2500-2F	25°							
	BX1500-8F	90°				BX2500-8F	107°							
Operation	Focus		Manual w/lock											
	Zoom		Fixed			Manual (w/lock)			Fixed		Manual (w/lock)			
	Iris		Fixed		DC drive		P-Iris		Fixed		DC drive		P-Iris	
Mechanical														
Temperature Detector	Yes													
Connectors	Power	2-pin terminal block, PoE												
	Ethernet	Ethernet (10/100 Base-T), Ethernet (10/100 Base-T), RJ-45 connector												
	Audio	1 In (built-in or external microphone), 1 Out (Stereo phone jack, 3.5 mm / 0.14")												
	Digital I/O	3-pin terminal block, pitch 2.5 mm / 0.1"												
	Auto Iris	Not functional		Yes			Not functional		Yes		Not functional			
Local Storage*	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported													
TV-Out	BNC connector (640 x 480 resolution)													
Mini USB	GV-WiFi Adapter or USB hard drive													
LED Indicator	2 LEDs: Power, Status													
General														
Environment Temperature	0°C ~ 50°C (32 °F ~ 122 °F)													
Humidity	10% to 90% (no condensation)													
Power Source	12V DC / PoE (IEEE 802.3af Class 3)													
Max. Power Consumption	9.5 W			6.27 W			7.99 W		6.42 W		9.5 W		6.77 W	
Regulatory	CE, FCC, RCM, RoHS compliant													
Dimensions (Without lens)	75.5 x 75 x 54 mm (2.97" x 2.95" x 2.13")													
Weight	300 g (0.66 lb)													
Note:	<ol style="list-style-type: none"> Product design and specifications are subject to change without notice. The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes). The TV-Out function only works under 640 x 480 resolution. For TV-Out to work properly, set the video resolution to 1280 x 1024 or lower. If both streams are enabled, the Sub Stream must be set to 640x 480. Memory card slot (local storage) is not supported in Argentina. Mind the following limitations and requirements for the mini USB port: <ul style="list-style-type: none"> The USB hard drive must be of 2.5" or 3.5", version 2.0 or above The USB hard drive's storage capacity must not exceed 2TB USB flash drives and USB hubs are not supported External power supply is required for the USB hard drive To connect a GV-WiFi Adapter, make sure it is connected before the camera is powered on. 													



Box Camera Specifications (Part 4)




		GV-BX12201
		
Camera		
Image Sensor		1/1.7" progressive scan CMOS
Picture Elements		4000 (H) x 3000 (V)
Minimum Illumination	Color	0.1 Lux
	B/W	0.05 Lux
	IR ON	0 Lux
Shutter Speed		Automatic, Manual (1/30 ~ 1/16000 sec)
White Balance		Automatic, Manual (2800 ~ 8500K)
Gain Control		Automatic
S/N Ratio		52 dB
WDR Pro (with WDR sensor)		No
Dynamic Range		Up to 72 dB
Operation		
Video Compression		H.264, MJPEG
Video Streaming		Dual streams from H.264 or MJPEG
Frame Rate		15 fps at 4000 x 3000
		30 fps at 3840 x 2160
Audio Compression		G.711, AAC (optional)
Sensor Input		1 Input (Dry Contact)
Alarm Output		1 Digital Output (200mA 5V DC)
Optical Lens		
Megapixel		Yes
Day/Night		Yes (with removable IR-cut filter)
Lens Type		Varifocal Lens
Focal Length		4.1 ~ 9 mm
Maximum Aperture		F/1.6
Mount		CS Mount
Image Format		1/1.8"
Horizontal FOV		109° ~ 50°
	Focus	Manual (w/lock)
Operation	Zoom	Manual (w/lock)
	Iris	DC drive
Mechanical		
Temperature Detector		Yes
Connectors	Power	2-pin terminal block, PoE
	Ethernet	RJ-45 connector
	Audio	1 In (Using the built-in microphone or externally connecting a microphone)
	Digital I/O	1 Out (Stereo phone jack, 3.5 mm / 0.14 in)
	Auto Iris	3-pin terminal block, pitch 2.5 mm (0.1")
	Local Storage*	Yes (with varifocal lens) Micro SD card slot (SDHC/SDXC/UHS-I, Class 10) *UHS-II card types are not supported. *Currently, the local storage function is not supported.
	TV-Out	BNC connector (640 x 480 resolution)
	Mini USB	GV-WiFi Adapter
LED Indicator		2 LEDs: Power, Status
General		
Environment Temperature		0 °C ~ 50 °C (32 °F ~ 122 °F)
Humidity		10% to 90% (no condensation)
Power Source		12V DC / 24V AC / PoE (IEEE 802.3af)
Max. Power Consumption		6 W
Regulatory		CE, FCC, RCM, RoHS compliant
Dimensions		Without lens: 120 x 75.2 x 54 mm (4.72" x 2.96" x 2.13")
		With lens: 184.1 x 75.2 x 64.1 mm (7.25" x 2.96" x 2.52")
Weight		545 g / 1.2 lb

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- The TV-Out function only works in 640 x 480 resolution. For TV-Out to work properly, you must set the video resolution to 1280 x 1024 or lower. If both streams are enabled, the Sub Stream must be set to 640 x 480.
- Memory card slot (local storage) is not supported in Argentina.



Ultra Box Camera Specifications





	GV-UBX1301 Series		GV-UBX2301 Series		GV-UBX3301 Series		
							
Camera							
Image Sensor	1/2.5" progressive scan CMOS						
Picture Elements	1280 (H) x 1024 (V)		1920 (H) x 1080 (V)		2048 (H) x 1536 (V)		
Minimum Illumination	Color	0.15 Lux					
	B/W	0.10 Lux					
	IR ON	0 Lux					
Shutter Speed	Auto, Manual (1/5 ~ 1/8000 sec)						
White Balance	Auto, Manual (2800K ~ 8500K)						
Gain Control	Automatic						
S/N Ratio	45dB						
Dynamic Range	Up to 72 dB						
Operation							
Video Compression	H.264, MJPEG						
Video Streaming	Dual streams						
Frame Rate	30 fps at 1280 x 1024		30 fps at 1920 x 1080		20 fps at 2048 x 1536		
Audio Compression	G.711, AAC (optional)						
Optical Lens							
Megapixel	Yes						
Day/Night	Yes (with removable IR-cut filter)						
Lens Type	Fixed						
Focal Length	GV-UBX1301-0F	2.8 mm	GV-UBX2301-0F	2.8 mm	GV-UBX3301-0F	2.8 mm	
	GV-UBX1301-1F	4 mm	GV-UBX2301-1F	4 mm	GV-UBX3301-1F	4 mm	
	GV-UBX1301-2F	8 mm	GV-UBX2301-2F	8 mm	GV-UBX3301-2F	8 mm	
Maximum Aperture	GV-UBX1301-0F	F/2.0	GV-UBX2301-0F	F/2.0	GV-UBX3301-0F	F/2.0	
	GV-UBX1301-1F	F/1.6	GV-UBX2301-1F	F/1.6	GV-UBX3301-1F	F/1.6	
	GV-UBX1301-2F		GV-UBX2301-2F		GV-UBX3301-2F		
Mount	M12, Pitch 0.5 mm						
Image Format	1/3"						
Horizontal FOV	GV-UBX1301-0F	69°	GV-UBX2301-0F	79°	GV-UBX3301-0F	80°	
	GV-UBX1301-1F	49°	GV-UBX2301-1F	58°	GV-UBX3301-1F	62°	
	GV-UBX1301-2F	25°	GV-UBX2301-2F	31°	GV-UBX3301-2F	33°	
Operation	Focus	Fixed					
	Zoom						
	Iris						
IR LED Quantity	4						
Max. IR Distance	10 m (32.81 ft)						
Mechanical							
Temperature Detector	Yes						
Connectors	Power	2-pin terminal block, PoE					
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector					
	Audio	1 In (built-in microphone), 1 Out (Stereo phone jack, 3.5 mm / 0.14")					
Local Storage*	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10)						
	*SDXC and UHS-I card types are not supported						
LED Indicator	2 LEDs: Power, Status						
General							
Environment Temperature	0°C ~ 40°C (32°F ~ 104°F)						
Humidity	10% to 90% (no condensation)						
Power Source	5V DC / PoE (IEEE 802.3af)						
Max. Power Consumption	6.5 W						
Regulatory	CE, FCC, RCM, RoHS compliant						
Dimensions (L X W X H) (Without lens)	95 x 45 x 40 mm (3.7" x 1.8" x 1.6")						
Weight	120 g (0.26 lb)						

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- The TV-Out function only works in 640 x 480 resolution. For TV-Out to work properly, you must set the video resolution to 1280 x 1024 or lower. If both streams are enabled, the Sub Stream must be set to 640 x 480.
- Memory card slot (local storage) is not supported in Argentina.



IR Arctic Box Camera Specifications (Part 1)





		GV-BX120D-E	GV-BX220D-E	GV-BX320D-E	GV-BX520D-E
					
Camera					
Image Sensor		1/3" progressive scan low lux CMOS		1/2.5" progressive scan CMOS	
Picture Elements		1280 (H) x 1024 (V)	1920 (H) x 1080 (V)	2048 (H) x 1536 (V)	2560 (H) x 1920 (V)
Minimum Illumination	Color	0.05 Lux		0.15 Lux	
	B/W	0.03 Lux		0.10 Lux	
	IR ON	0 Lux			
Shutter Speed		Auto, Manual (1/5 ~ 1/8000 sec)			
White Balance		Auto, Manual (2800K ~ 8500K)			
Gain Control		Automatic			
S/N Ratio		50 dB			45 dB
Dynamic Range		Up to 72 dB			
Operation					
Video Compression		H.264, MJPEG			
Video Streaming		Dual streams			
Frame Rate		30 fps at 1280 x 1024	30 fps at 1920 x 1080	20 fps at 2048 x 1536	10 fps at 2560 x 1920
Audio Compression		G.711, AAC (optional)			
Optical Lens					
Megapixel		Yes			
Day/Night		Yes (with removable IR-cut filter)			
Lens Type		Varifocal Lens			
Focal Length		2.8 ~ 12 mm	2.8 ~ 6 mm	4.5 ~ 10 mm	
Maximum Aperture		F/1.4	F/1.3	F/1.6	
Mount		CS Mount			
Image Format		1/3"			1/2"
Operation	Focus	Manual (w/lock)			
	Zoom	Manual (w/lock)			
	Iris	DC drive			Manual (w/lock)
IR LED Quantity		4 IR LEDs			
Max. IR Distance		15 m (50 ft)			
Mechanical					
Camera	Pan	0° ~ 330°			
Angle	Tilt	0° ~ 90°			
Adjustment	Rotate	No			
Temperature	Detector	Yes			
Connectors	Power	PoE			
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector			
	Audio	1 In (external microphone)			
		1 Out (Stereo phone jack, 3.5 mm / 0.14")			
	Auto Iris	DC drive			Not functional
TV-Out	BNC connector (640 x 480 resolution)				
LED Indicator		1 LED: Status			
General					
Environment Temperature		-40 °C ~ 50 °C (-40 °F ~ 122 °F)			
Humidity		10% to 90% (no condensation)			
Power Source		PoE (IEEE 802.3 at)			
Max. Power Consumption		24 W			
Regulatory		CE, FCC, RCM, RoHS compliant			
Dimensions (L X W X H) (Without lens)		100.5 x 100.5 x 317.5 mm (3.96" x 3.96" x 12.5")			
Weight		3.2 Kg (7.1 lb)			
Ingress Protection		IP67			
Vandal Resistance		IK10 for metal casing			
Heater On		-40°C ~ 8°C (-40°F ~ 46.4°F)			
Fan		Constantly on			

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- Memory card slot (local storage) is not supported in Argentina.



IR Arctic Box Camera Specifications (Part 2)



		GV-BX1500-E	GV-BX2400-E	GV-BX3400-E	GV-BX5310-E
					
Camera					
Image Sensor		1/3" progressive scan super low lux CMOS		1/3.2" progressive scan CMOS	
Picture Elements		1280 (H) x 1024 (V)		2048 (H) x 1536 (V)	
Minimum Illumination	Color	0.01 Lux		0.08 Lux	
	B/W	0.01 Lux		0.05 Lux	
	IR ON			0 Lux	
Shutter Speed		Auto, Manual (1/5 ~ 1/8000 sec)			
White Balance		Auto, Manual (2800K ~ 8500K)			
Gain Control		Automatic			
S/N Ratio		55 dB		47 dB	
WDR Pro (with WDR Sensor)		N/A		Yes	
Dynamic Range		Up to 72 dB		Up to 100 dB	
Operation					
Video Compression		H.264, MJPEG			
Video Streaming		Dual streams			
Frame Rate		30 fps at 1280 x 1024		20 fps at 2048 x 1536	
Audio Compression		G.711, AAC (optional)			
Optical Lens					
Megapixel		Yes			
Day/Night		Yes (with removable IR-cut filter)			
Lens Type		Varifocal Lens			
Focal Length		3 ~ 10.5 mm		4.5 ~ 10 mm	
Maximum Aperture		F/1.4		F/1.6	
Mount		CS Mount			
Image Format		1/2.7"		1/2"	
Horizontal FOV		81° ~ 29°		78° ~ 28°	
Operation	Focus	Manual (w/lock)			
	Zoom	Manual (w/lock)			
	Iris	DC drive		Manual (w/lock)	
IR LED Quantity		4 IR LEDs			
Max. IR Distance		15 m (50 ft)			
Mechanical					
Camera Angle Adjustment	Pan	0° ~ 330°			
	Tilt	0° ~ 90°			
	Rotate	No			
Temperature Detector		Yes			
Connectors	Power	PoE			
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector			
	Audio	1 In (external microphone), 1 Out (Stereo phone jack, 3.5 mm / 0.14")			
	Auto Iris	DC drive		Not functional	
	TV-Out	BNC connector (640 x 480 resolution)			
LED Indicator		2 LEDs: Power, Status			
General					
Environment Temperature	Start-up	-30 °C ~ 50 °C (-22°F ~ 122°F)			
	Operation	-40 °C ~ 50 °C (-40°F ~ 122°F)			
Humidity		10% to 90% (no condensation)			
Power Source		PoE (IEEE 802.3 at)			
Max. Power Consumption		20 W		23 W	
Regulatory		CE, FCC, RCM, RoHS compliant			
Dimensions (L X W X H) (Without lens)		100.5 x 100.5 x 317.5 mm (3.96" x 3.96" x 12.5")			
Weight		3.2 Kg (7.1 lb)			
Ingress Protection		IP67			
Vandal Resistance		IK10 for metal casing			
Heater On		-40°C ~ 8°C (-40°F ~ 46.4°F)			
Fan		Constantly on			

Note:

1. Product design and specifications are subject to change without notice.
2. The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
3. **Memory card slot (local storage) is not supported in Argentina.**



IR Arctic Box Camera Specifications (Part 3)





		GV-BX2510-E (Coming)	GV-BX5310-E (Coming)
			
Camera			
Image Sensor		1/2.8" progressive scan super low lux CMOS	1/2.5" progressive scan CMOS
Picture Elements		1920 (H) x 1080 (V)	2560 (H) x 1920 (V)
Minimum Illumination	Color	0.02 Lux	0.15 Lux
	B/W	0.02 Lux	0.10 Lux
	IR ON	0 Lux	
Shutter Speed		Auto, Manual (1/5 ~ 1/8000 sec)	
White Balance		Auto, Manual (2800K ~ 8500K)	
Gain Control		Automatic	
S/N Ratio		52 dB	45 dB
WDR Pro (with WDR Sensor)		N/A	N/A
Dynamic Range		Up to 72 dB	Up to 72 dB
Operation			
Video Compression		H.264, MJPEG	
Video Streaming		Dual streams	
Frame Rate		30 fps at 1920 x 1080	10 fps at 2560 x 1920
Audio Compression		G.711, AAC (optional)	
Sensor Input		1 input (Dry Contact)	
Alarm Output		1 digital output (200mA 5V DC)	
Optical Lens			
Megapixel		Yes	
Day/Night		Yes (with removable IR-cut filter)	
Lens Type		Motorized Varifocal Lens	
Focal Length		3.7 ~ 9 mm	4.5 ~ 9 mm
Maximum Aperture		F/1.2	F/1.2
Mount		Ø14 mm	
Image Format		1/2.7"	1/2.7"
Horizontal FOV		85° ~ 36°	70° ~ 39°
Operation	Focus	Auto focus	
	Zoom	2.4X optical zoom	2X optical zoom
	Iris	P-Iris	
IR LED Quantity		4 IR LEDs	
Max. IR Distance		70 m (230 ft)	50 m (164 ft)
Mechanical			
Camera Angle Adjustment	Pan	0° ~ 330°	
	Tilt	0° ~ 90°	
	Rotate	No	
Temperature Detector		Yes	
Connectors	Power	2-pin terminal block, PoE	
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector	
	Audio	1 In (external microphone), 1 Out (Stereo phone jack, 3.5 mm / 0.14")	
	Digital I/O	I/O wires	
	Local Storage	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported	
TV-Out		BNC connector (640 x 480 resolution)	
LED Indicator		2 LEDs: Power, Status	
General			
Environment Temperature	Start-up	-30 °C ~ 50 °C (-22°F ~ 122°F)	
	Operation	-40 °C ~ 50 °C (-40°F ~ 122°F)	
Humidity		10% to 90% (no condensation)	
Power Source		AC 24V, DC 48V, PoE++ (50W)	
Max. Power Consumption		50 W	
Regulatory		CE, FCC, RCM, RoHS compliant	
Dimensions (L X W X H)	Camera Body	406 x 145 x 109.5 mm (16" x 5.7" x 4.3")	
	Cable Length	1 m (39.4")	
Weight		3.32 Kg (7.32 lb)	
Ingress Protection		IP67	
Vandal Resistance		IK10 for metal casing	
Heater On		On: -40 °C ~ -4 °C (-40 °F ~ 24.8 °F); Off: -3 °C (26.6 °F)	
Fan		Constantly on	

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- Memory card slot (local storage) is not supported in Argentina.



Bullet Camera Specifications (Part 1)





	GV-BL120D	GV-BL130D	GV-BL220D	GV-BL320D
				
Camera				
Image Sensor	1/3" progressive scan low lux CMOS		1/2.5" progressive scan CMOS	
Picture Elements	1280 (H) x 1024 (V)		1920 (H) x 1080 (V)	2048 (H) x 1536 (V)
Minimum Illumination	Color	0.05 Lux	0.15 Lux	
	B/W	0.03 Lux	0.10 Lux	
	IR ON	0 Lux		
Shutter Speed	Auto, Manual (1/5 ~ 1/8000sec)			
White Balance	Auto, Manual (2800K ~ 8500K)			
Gain Control	Automatic			
S/N Ratio	50 dB			45 dB
Dynamic Range	Up to 72 dB			
Operation				
Video Compression	H.264, MJPEG			
Video Streaming	Dual streams			
Frame Rate	30 fps at 1280 x 1024		30 fps at 1920 x 1080	20 fps at 2048 x 1536
Audio Compression	G.711, AAC (optional)			
Sensor Input	1 input (Dry Contact)			
Alarm Output	1 digital output (200mA 5V DC)			
Optical Lens				
Megapixel	Yes			
Day/Night	Yes (with removable IR-cut filter)			
Lens Type	Varifocal Lens			
Focal Length	3 ~ 9 mm			
Maximum Aperture	F/1.2			
Mount	Ø14 mm			
Image Format	1/2.7"			
Operation	Focus	Manual (w/lock)		
	Zoom	Manual (w/lock)		
	Iris	DC drive		
IR LED Quantity	16 IR LEDs			
Max. IR Distance	15 m (50 ft)			
Mechanical				
Camera Angle Adjustment	Pan	0° ~ 360°		
	Tilt	90° ~ 180°		
	Rotate	0° ~ 360°		
Temperature Detector	Yes			
Connectors	Power	2-pin terminal block, PoE		
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector		
	Audio	1 In (RCA female for microphone); 1 Out (RCA female for speaker)		
	Digital I/O	I/O Wire		
	Local Storage*	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported		
General				
Environment Temperature	-20 °C ~ 50 °C (-4 °F ~ 122 °F)			
Humidity	10% to 90% (no condensation)			
Power Source	12V DC / 24V AC / PoE (IEEE 802.3af)			
Max. Power Consumption	12W			
Regulatory	CE, FCC, RCM, RoHS compliant			
Dimensions	Camera Body	277.5 x 87.75 x 148.95 mm (10.9" x 3.45" x 5.86")		
	Cable Length	1 m (3.28 ft)		
	Max. Cable Diameter	Ø 7.1 mm (0.28")		
	Max. Connector Diameter	Ø 25.2 mm (0.99")		
Weight	1.35 kg (2.98 lb)			
Ingress Protection	IP66			

Note:

1. Product design and specifications are subject to change without notice.
2. The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
3. **Memory card slot (local storage) is not supported in Argentina.**



Bullet Camera Specifications (Part 2)





		GV-BL1500	GV-BL2400	GV-BL2500	GV-BL3400
					
Camera					
Image Sensor		1/3" progressive scan super low lux CMOS	1/3.2" progressive scan CMOS	1/2.8" progressive scan super low lux CMOS	1/3.2" progressive scan CMOS
Picture Elements		1280 (H) x 1024 (V)	1920 (H) x 1080 (V)		2048 (H) x 1536 (V)
Minimum Illumination	Color	0.01 Lux	0.08 Lux	0.02 Lux	0.08 Lux
	B/W	0.01 Lux	0.05 Lux	0.02 Lux	0.05 Lux
	IR ON	0 Lux			
Shutter Speed		Auto, Manual (1/5 ~ 1/8000sec)			
White Balance		Auto, Manual (2800K ~ 8500K)			
Gain Control		Automatic			
S/N Ratio		55 dB	47 dB	52 dB	47 dB
WDR Pro (with WDR sensor)		N/A	Yes	N/A	Yes
Dynamic Range		Up to 72 dB	Up to 100 dB	Up to 72 dB	Up to 100 dB
Operation					
Video Compression		H.264, MJPEG			
Video Streaming		Dual streams			
Frame Rate		30 fps at 1280 x 1024	30 fps at 1920 x 1080		20 fps at 2048 x 1536
Audio Compression		G.711, AAC (optional)			
Sensor Input		1 input (Dry Contact)			
Alarm Output		1 digital output (200mA 5V DC)			
Optical Lens					
Megapixel		Yes			
Day/Night		Yes (with removable IR-cut filter)			
Lens Type		Varifocal Lens			
Focal Length		3 ~ 9 mm			
Maximum Aperture		F/1.2			
Mount		Ø14 mm			
Image Format		1/2.7"			
Horizontal FOV		90° ~ 32°	82° ~ 30°	103° ~ 36°	86° ~ 31°
Operation	Focus	Manual (w/lock)			
	Zoom	Manual (w/lock)			
	Iris	DC drive	DC drive	DC drive	DC drive
IR LED Quantity		16 IR LEDs			
Max. IR Distance		70 m (230 ft)	50 m (164 ft)		
Mechanical					
Camera Angle Adjustment	Pan	0° ~ 360°			
	Tilt	90° ~ 180°			
	Rotate	0° ~ 360°			
Temperature Detector		Yes			
Connectors	Power	2-pin terminal block, PoE			
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector			
	Audio	1 In (RCA female for microphone); 1 Out (RCA female for speaker)			
	Digital I/O	I/O Wire			
Local Storage*		Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported			
General					
Environment Temperature		-30 °C ~ 50 °C (-22 °F ~ 122 °F)			
Humidity		10% to 90% (no condensation)			
Power Source		12V DC / 24V AC / PoE (IEEE 802.3af)			
Max. Power Consumption		7.68 W	7.2 W	8 W	7.2 W
Regulatory		CE, FCC, RCM, RoHS compliant			
Dimensions	Camera Body	277.5 x 87.75 x 148.95 mm (10.9" x 3.45" x 5.86")			
	Cable Length	1 m (3.28 ft)			
	Max. Cable Diameter	Ø 7.1 mm (0.28")			
	Max. Connector Diameter	Ø 25.2 mm (0.99")			
Weight		1.4 Kg (3.08 lb)	1.35 kg (2.98 lb)	1.4 Kg (3.08 lb)	1.35 kg (2.98 lb)
Ingress Protection		IP67			
Vandal Resistance		IK10 for metal casing			

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- Memory card slot (local storage) is not supported in Argentina.



Bullet Camera Specifications (Part 3)




		GV-BL1210	GV-BL1510 (Coming)	GV-BL3410	GV-BL5310
					
Camera					
Image Sensor		1/3" progressive scan low lux CMOS	1/3" progressive scan super low lux CMOS	1/3.2" progressive scan CMOS	1/2.5" progressive scan CMOS
Picture Elements		1280 (H) x 1024 (V)		2048 (H) x 1536 (V)	2560 (H) x 1920 (V)
Minimum Illumination	Color	0.05 Lux	0.01 Lux	0.08 Lux	0.15 Lux
	B/W	0.03 Lux	0.01 Lux	0.05 Lux	0.10 Lux
	IR ON	0 Lux			
Shutter Speed		Auto, Manual (1/5 ~ 1/8000sec)			
White Balance		Auto, Manual (2800K ~ 8500K)			
Gain Control		Automatic			
S/N Ratio		50 dB	55 dB	47 dB	45 dB
WDR Pro (with WDR sensor)		N/A		Yes	N/A
Dynamic Range		Up to 72 dB		Up to 100 dB	Up to 72 dB
Operation					
Video Compression		H.264, MJPEG			
Video Streaming		Dual streams			
Frame Rate		30 fps at 1280 x 1024		20 fps at 2048 x 1536	10 fps at 2560 x 1920
Audio Compression		G.711, AAC (optional)			
Sensor Input		1 input (Dry Contact)			
Alarm Output		1 digital output (200mA 5V DC)			
Optical Lens					
Megapixel		Yes			
Day/Night		Yes (with removable IR-cut filter)			
Lens Type		Motorized Varifocal Lens			
Focal Length		3 ~ 9 mm			4.5 ~ 9 mm
Maximum Aperture		F/1.2			
Mount		Ø14 mm			
Image Format		1/2.7"			
Horizontal FOV		86° ~ 32°	90° ~ 32°	86° ~ 31°	70° ~ 39°
Operation	Focus	Auto Focus			
	Zoom	3X Optical Zoom			2X Optical Zoom
	Iris	DC drive			
IR LED Quantity		16 IR LEDs			
Max. IR Distance		40 m (131 ft)	70 m (230 ft)	50 m (164 ft)	40 m (131 ft)
Mechanical					
Camera Angle Adjustment	Pan	0° ~ 360°			
	Tilt	90° ~ 180°			
	Rotate	0° ~ 360°			
Temperature Detector		Yes			
Connectors	Power	2-pin terminal block, PoE			
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector			
	Audio	1 In (RCA female for microphone)			
		1 Out (RCA female for speaker)			
	Digital I/O	I/O Wire			
Local Storage*		Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported			
General					
Environment Temperature		-20 °C ~ 50 °C (-4 °F ~ 122 °F)			
Humidity		10% to 90% (no condensation)			
Power Source		12V DC / 24V AC / PoE (IEEE 802.3af)			
Max. Power Consumption		11.52 W	13.8 W	12.48 W	
Regulatory		CE, FCC, RCM, RoHS compliant			
Dimensions	Camera Body	289.02 x 87.75 x 148.95 mm (11.4" x 3.45" x 5.86")			
	Cable Length	1 m (3.28 ft)			
	Max. Cable Diameter	Ø 7.1 mm (0.28")			
	Max. Connector Diameter	Ø 25.2 mm (0.99")			
Weight		1.4 Kg (3.08 lb)			
Ingress Protection		IP67			
Vandal Resistance		IK10 for metal casing			

Note:

1. Product design and specifications are subject to change without notice.
2. The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
3. Memory card slot (local storage) is not supported in Argentina.



Ultra Bullet Camera Specifications (Part 1)




	GV-UBL 1211	GV-UBL2411	GV-UBL3411
			
Camera			
Image Sensor	1/3" progressive scan low lux CMOS	1/3.2" progressive scan CMOS	1/3.2" progressive scan CMOS
Picture Elements	1280 (H) x 1024 (V)	1920 (H) x 1080 (V)	2048 (H) x 1536 (V)
Minimum Illumination	Color	0.05 Lux	0.08 Lux
	B/W	0.03 Lux	0.05 Lux
	IR ON		0 Lux
Shutter Speed		Auto, Manual (1/5 ~ 1/8000sec)	
White Balance		Auto, Manual (2800K ~ 8500K)	
Gain Control		Automatic	
S/N Ratio	50 dB	47 dB	47 dB
WDR Pro (with WDR sensor)	N/A	Yes	Yes
Dynamic Range	Up to 72 dB	Up to 100 dB	Up to 100 dB
Operation			
Video Compression		H.264, MJPEG	
Video Streaming		Dual streams	
Frame Rate	30 fps at 1280 x 1024	30 fps at 1920 x 1080	20 fps at 2048 x 1536
Sensor Input		1 input (Dry Contact)	
Alarm Output		1 digital output (200mA 5V DC)	
Optical Lens			
Megapixel		Yes	
Day/Night		Yes (with removable IR-cut filter)	
Lens Type		Motorized Varifocal Lens	
Focal Length		3~9 mm	
Maximum Aperture		F/1.2	
Mount		Ø14 mm	
Image Format		1/2.7"	
Horizontal FOV	86° ~ 32°	82° ~ 30°	86° ~ 31°
Operation	Focus	Auto Focus	
	Zoom	3X Optical Zoom	
	Iris	DC Drive	
IR LED Quantity		4 IR LEDs	
Max. IR Distance		10 m (32.81 ft)	
Mechanical			
Temperature Detector		Yes	
Connectors	Power	2-pin terminal block, PoE	
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector (Waterproof or smaller-sized Non-Waterproof)	
Local Storage*	Digital I/O	I/O Wire	
	Local Storage*	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported	
General			
Environment Temperature		-10 °C ~ 45 °C (14 °F ~ 113 °F)	
Humidity		10% to 90% (no condensation)	
Power Source		5V DC / PoE (IEEE 802.3af)	
Max. Power Consumption	6.94 W	6.94 W	6.94 W
Regulatory		CE, FCC, RCM, RoHS compliant	
Dimensions		148.75 x 65 x 69 mm (5.9" x 2.6" x 2.7")	
Weight		850 g (1.9 lb)	
Ingress Protection		IP67	
Vandal Resistance		IK10 for metal casing	

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- Memory card slot (local storage) is not supported in Argentina.



Ultra Bullet Camera Specifications (Part 2)








		GV-UBL1301 Series		GV-UBL2401 Series		GV-UBL3401 Series	
							
Camera							
Image Sensor		1/2.5" progressive scan CMOS		1/3.2" progressive scan CMOS			
Picture Elements		1280 (H) x 1024 (V)		1920 (H) x 1080 (V)		2048 (H) x 1536 (V)	
Minimum Illumination	Color	0.15 Lux		0.08 Lux			
	B/W	0.10 Lux		0.05 Lux			
	IR ON	0 Lux					
Shutter Speed		Auto, Manual (1/5 ~ 1/8000sec)					
White Balance		Auto, Manual (2800K ~ 8500K)					
Gain Control		Automatic					
S/N Ratio		45 dB		47 dB			
WDR Pro (with WDR sensor)		N/A		Yes			
Dynamic Range		Up to 72 dB		Up to 100 dB			
Operation							
Video Compression		H.264, MJPEG					
Video Streaming		Dual streams					
Frame Rate		30 fps at 1280 x 1024		30 fps at 1920 x 1080		20 fps at 2048 x 1536	
Sensor Input		1 input (Dry Contact)					
Alarm Output		1 digital output (200mA 5V DC)					
Optical Lens							
Megapixel		Yes					
Day/Night		Yes (with removable IR-cut filter)					
Lens Type		Fixed Lens					
Focal Length	GV-UBL1301-0F	2.8 mm	GV-UBL2401-0F	2.8 mm	GV-UBL3401-0F	2.8 mm	
	GV-UBL1301-1F	4 mm	GV-UBL2401-1F	4 mm	GV-UBL3401-1F	4 mm	
	GV-UBL1301-2F	8 mm	GV-UBL2401-2F	8 mm	GV-UBL3401-2F	8 mm	
	GV-UBL1301-3F	12 mm	GV-UBL2401-3F	12 mm	GV-UBL3401-3F	12 mm	
Maximum Aperture	GV-UBL1301-0F	F/2.0	GV-UBL2401-0F	F/2.0	GV-UBL3401-0F	F/2.0	
	GV-UBL1301-1F	F/1.5	GV-UBL2401-1F	F/1.5	GV-UBL3401-1F	F/1.5	
	GV-UBL1301-2F	F/1.6	GV-UBL2401-2F	F/1.6	GV-UBL3401-2F	F/1.6	
	GV-UBL1301-3F	F/1.6	GV-UBL2401-3F	F/1.6	GV-UBL3401-3F	F/1.6	
Mount		M12					
Image Format		1/3"					
Horizontal FOV	GV-UBL1301-0F	69°	GV-UBL2401-0F	79°	GV-UBL3401-0F	80°	
	GV-UBL1301-1F	49°	GV-UBL2401-1F	58°	GV-UBL3401-1F	62°	
	GV-UBL1301-2F	25°	GV-UBL2401-2F	31°	GV-UBL3401-2F	33°	
	GV-UBL1301-3F	16°	GV-UBL2401-3F	20°	GV-UBL3401-3F	21°	
Operation	Focus	Fixed					
	Zoom	Fixed					
	Iris	Fixed					
IR LED Quantity		4 IR LEDs					
Max. IR Distance		10 m (32.81 ft)					
Mechanical							
Temperature Detector		Yes					
Connectors	Power	2-pin terminal block, PoE					
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector (Waterproof or smaller-sized Non-Waterproof)					
	Digital I/O	I/O Wire					
Local Storage*		Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported					
General							
Environment Temperature	Start-up	-20 °C ~ 45 °C (-4 °F ~ 113 °F)		-20 °C ~ 45 °C (-4 °F ~ 113 °F)			
	Operation	-30 °C ~ 45 °C (-22 °F ~ 113 °F)					
Humidity		10% to 90% (no condensation)					
Power Source		5V DC / PoE (IEEE 802.3af)					
Max. Power Consumption		5.52W					
Regulatory		CE, FCC, RCM, RoHS compliant					
Dimensions		124 x 65 x 69 mm (4.9" x 2.6" x 2.7")					
Weight		730 g (1.6 lb)					
Ingress Protection		IP67					
Vandal Resistance		IK10 for metal casing					

Note:

1. Product design and specifications are subject to change without notice.
2. The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
3. **Memory card slot (local storage) is not supported in Argentina.**



Vandal Proof Dome Specifications (Part 1)





		(IK10+, Transparent Cover) - GV-VD120D - GV-VD121D (IK7, Transparent Cover) - GV-VD122D - GV-VD123D	(IK10+, Transparent Cover) GV-VD220D GV-VD221D (IK7, Transparent Cover) - GV-VD222D - GV-VD223D	(IK10+, Transparent Cover) - GV-VD320D - GV-VD321D (IK7, Transparent Cover) - GV-VD322D - GV-VD323D	GV-VD1500 (IK10+, Transparent Cover)	GV-VD2400 (IK10+, Transparent Cover)	GV-VD2500 (IK10+, Transparent Cover)	GV-VD3400 (IK10+, Transparent Cover)	
Camera									
Image Sensor		1/2.5" progressive scan CMOS		1/3" progressive scan super low lux CMOS	1/3.2" progressive scan CMOS	1/2.8" progressive scan super low lux CMOS	1/3.2" progressive scan CMOS		
Picture Elements		1280 (H) x 1024 (V)	1920 (H) x 1080 (V)	2048 (H) x 1536 (V)	1280 (H) x 1024 (V)	1920 (H) x 1080 (V)	2048 (H) x 1536 (V)		
Minimum Illumination	Color	0.05 Lux	0.15 Lux		0.01 Lux	0.08 Lux	0.02 Lux	0.08 Lux	
	B/W	0.03 Lux	0.10 Lux		0.01 Lux	0.05 Lux	0.02 Lux	0.05 Lux	
	IR ON	0 Lux							
Shutter Speed		Auto, Manual (1/5 ~ 1/8000 sec)							
White Balance		Auto, Manual (2800K ~ 8500K)							
Gain Control		Automatic							
S/N Ratio		50 dB	45 dB		55 dB	47 dB	52 dB	47 dB	
WDR Pro (with WDR sensor)		N/A				Yes	N/A	Yes	
Dynamic Range		Up to 72 dB				Up to 100 dB	Up to 72 dB	Up to 100 dB	
Operation									
Video Compression		H.264, MJPEG							
Video Streaming		Dual streams							
Frame Rate		30 fps at 1280 x 1024	30 fps at 1920 x 1080	20 fps at 2048 x 1536	30 fps at 1280 x 1024	30 fps at 1920 x 1080	30 fps at 1920 x 1080	20 fps at 2048 x 1536	
Audio Compression		G.711, AAC (optional)							
Sensor Input		1 Input (Dry Contact)							
Alarm Output		1 Digital output (200mA 5V DC)							
Optical Lens									
Megapixel		Yes							
Day/Night		Yes (with removable IR-cut filter)							
Lens Type		Varifocal Lens							
Focal Length		3 ~ 9 mm							
Maximum Aperture		F/1.3			F/1.2				
Mount		Ø14 mm							
Image Format		1/3"							
Horizontal FOV		86° ~ 32°	82° ~ 30°	86° ~ 31°	90° ~ 32°	82° ~ 30°	103° ~ 36°	86° ~ 31°	
Operation	Focus	Manual (w/lock)							
	Zoom	Manual (w/lock)							
	Iris	DC drive							
IR LED Quantity		10 IR LEDs							
Max. IR Distance		15 m (50 ft)				30 m (98.4 ft)			
Mechanical									
Camera Angle Adjustment	Pan	0° ~ 350°							
	Tilt	10° ~ 90°							
	Rotate	0° ~ 340°							
Temperature Detector		Yes							
Connectors	Power	2-pin terminal block, PoE							
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector							
	Audio	1 In (RCA female for microphone), 1 Out (RCA female for speaker)							
	Digital I/O	I/O Wire							
	Local Storage*	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported							
TV-Out		BNC connector (640 x 480 resolution)							
LED Indicator		2 LEDs: Power, Status							
General									
Environment Temperature		-30 °C ~ 50 °C (-22 °F ~ 122 °F)							
Humidity		10% to 90% (no condensation)							
Power Source		12V DC / 24V AC / PoE (IEEE 802.3af)							
Max. Power Consumption		12 W							
Regulatory		CE, FCC, RCM, RoHS compliant							
Dimensions	Camera Body	Ø 165 x 125 mm (6.49" x 4.92")							
	Cable Length	1 m (3.28 ft)							
	Cable Diameter	Ø 16.7 mm (0.66")							
	Max. Connector Diameter	Ø 16.7 mm (0.66")							
	Weight		1.7 kg (3.75 lb)						
Ingress Protection		IP67							

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- The TV-Out function only works in 640 x 480 resolution. For TV-Out to work properly, you must set the video resolution to 1280 x 1024 or lower. If both streams are enabled, the Sub Stream must be set to 640 x 480.
- Memory card slot (local storage) is not supported in Argentina.



Vandal Proof Dome Specifications (Part 2)






		GV-VD1530	GV-VD2430	GV-VD2530	GV-VD3430
					
Camera					
Image Sensor		1/3" progressive scan super low lux CMOS	1/3.2" progressive scan CMOS	1/2.8" progressive scan super low lux CMOS	1/3.2" progressive scan CMOS
Picture Elements		1280 (H) x 1024 (V)	1920 (H) x 1080 (V)	1920 (H) x 1080 (V)	2048 (H) x 1536 (V)
Minimum Illumination	Color	0.01 Lux	0.08 Lux	0.02 Lux	0.08 Lux
	B/W	0.01 Lux	0.05 Lux	0.02 Lux	0.05 Lux
	IR ON	0 Lux			
Shutter Speed		Auto, Manual (1/5 ~ 1/8000 sec)			
White Balance		Auto, Manual (2800K ~ 8500K)			
Gain Control		Automatic			
S/N Ratio		55 dB	47 dB	52 dB	47 dB
WDR Pro (with WDR sensor)		N/A	Yes	N/A	Yes
Dynamic Range		Up to 72 dB	Up to 100 dB	Up to 72 dB	Up to 100 dB
Operation					
Video Compression		H.264, MJPEG			
Video Streaming		Dual streams			
Frame Rate		30 fps at 1280 x 1024	30 fps at 1920 x 1080	30 fps at 1920 x 1080	20 fps at 2048 x 1536
Audio Compression		G.711, AAC (optional)			
Sensor Input		1 Input (Dry Contact)			
Alarm Output		1 Output (200mA 5V DC)			
Optical Lens					
Megapixel		Yes			
Day/Night		Yes (with removable IR-cut filter)			
Lens Type		Varifocal Lens			
Focal Length		3 ~ 9 mm			
Maximum Aperture		F/1.2			
Mount		Ø14 mm			
Image Format		1/2.7"			
Horizontal FOV		90° ~ 32°	82° ~ 30°	103° ~ 36°	86° ~ 31°
Operation	Focus	Manual (w/lock)			
	Zoom	Manual (w/lock)			
	Iris	DC drive			
High Power LED		6 IR LEDs			
Max. IR Distance		30 m (98.4 ft)	20 m (65.6 ft)	25 m (82.0 ft)	20 m (65.6 ft)
Mechanical					
Camera	Pan	-90° ~ 90°			
Angle	Tilt	0° ~ 85°			
Adjustment	Rotate	0° ~ 350°			
Temperature Detector		Yes			
Power		2-pin terminal block, PoE			
Ethernet		Ethernet (10/100 Base-T), RJ-45 connector			
Audio		1 In (3.5 mm phone jack for microphone), 1 Out (3.5 mm phone jack for speaker)			
Connectors	Digital I/O	3-pin terminal block, pitch 2.5 mm (0.1")			
	Local Storage*	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported			
	TV-Out	BNC connector (640 x 480 resolution)			
LED Indicator		2 LEDs: Power, Status			
General					
Environment	Start-up	-20 °C ~ 50 °C (-4 °F ~ 122 °F)			
Temperature	Operation	-30 °C ~ 50 °C (-22 °F ~ 122 °F)			
Humidity		10% to 90% (no condensation)			
Power Source		12V DC / 24V AC / PoE (IEEE 802.3at)			
Max. Power Consumption		15.4 W			
Regulatory		CE, FCC, RCM, RoHS compliant			
Dimensions		Ø176.5 x 118 mm (6.9" x 4.6")			
Weight		1.76 kg (3.88 lb)			
Ingress Protection		IP67			
Vandal Resistance		IK10+			

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- The TV-Out function only works in 640 x 480 resolution. For TV-Out to work properly, you must set the video resolution to 1280 x 1024 or lower. If both streams are enabled, the Sub Stream must be set to 640 x 480.
- Memory card slot (local storage) is not supported in Argentina.



Vandal Proof Dome Specifications (Part 3)



	GV-VD1540	GV-VD2440	GV-VD2540	GV-VD3440	GV-VD5340
					
Camera					
Image Sensor	1/3" progressive scan super low lux CMOS	1/3.2" progressive scan CMOS	1/2.8" progressive scan super low lux CMOS	1/3.2" progressive scan CMOS	1/2.5" progressive scan CMOS
Picture Elements	1280 (H) x 1024 (V)	1920 (H) x 1080 (V)	1920 (H) x 1080 (V)	2048 (H) x 1536 (V)	2560 (H) x 1920 (V)
Minimum Illumination	Color 0.01 Lux B/W 0.01 Lux IR ON 0 Lux	0.08 Lux 0.05 Lux	0.02 Lux	0.08 Lux 0.05 Lux	0.15 Lux 0.10 Lux
Shutter Speed	Auto, Manual (1/5 ~ 1/8000 sec)				
White Balance	Auto, Manual (2800K ~ 8500K)				
Gain Control	Automatic				
S/N Ratio	55 dB	47 dB	52 dB	47 dB	45 dB
WDR Pro (with WDR sensor)	N/A	Yes	N/A	Yes	N/A
Dynamic Range	Up to 72 dB	Up to 100 dB	Up to 72 dB	Up to 100 dB	Up to 72 dB
Operation					
Video Compression	H.264, MJPEG				
Video Streaming	Dual streams				
Frame Rate	30 fps at 1280 x 1024	30 fps at 1920 x 1080	30 fps at 1920 x 1080	20 fps at 2048 x 1536	10 fps at 2560 x 1920
Audio Compression	G.711, AAC (optional)				
Sensor Input	1 Input (Dry Contact)				
Alarm Output	1 Output (200mA 5V DC)				
Optical Lens					
Megapixel	Yes				
Day/Night	Yes (with removable IR-cut filter)				
Lens Type	Motorized Varifocal Lens				
Focal Length	3 ~ 9 mm				3.3 ~ 9 mm
Maximum Aperture	F/1.2				
Mount	Ø14 mm				
Image Format	1/2.7"				
Horizontal FOV	90° ~ 32°	82° ~ 30°	103° ~ 36°	86° ~ 31°	100° ~ 39°
Operation	Auto Focus				
Zoom	3x Optical Zoom				
Iris	DC drive				
High Power LED	6 IR LEDs				
Max. IR Distance	30 m (98.4 ft)	20 m (65.6 ft)	25 m (82.0 ft)	20 m (65.6 ft)	
Mechanical					
Camera	Pan				-90° ~ 90°
Angle	Tilt				0° ~ 85°
Adjustment	Rotate				0° ~ 350°
Temperature	Detector				Yes
Connectors	Power	2-pin terminal block, PoE			
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector			
	Audio	1 In (3.5 mm phone jack for microphone), 1 Out (3.5 mm phone jack for speaker)			
	Digital I/O	3-pin terminal block, pitch 2.5 mm (0.1")			
	Local Storage*	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported			
TV-Out	BNC connector (640 x 480 resolution)				
LED Indicator	2 LEDs: Power, Status				
General					
Environment Temperature	-20 °C ~ 50 °C (-4 °F ~ 122 °F)				
Humidity	10% to 90% (no condensation)				
Power Source	12V DC / 24V AC / PoE (IEEE 802.3at)				
Max. Power Consumption	22.48 W				
Regulatory	CE, FCC, RCM, RoHS compliant				
Dimensions	Ø176.5 x 118 mm (6.9" x 4.6")				
Weight	1.83 kg (4.03 lb)				
Ingress Protection	IP67				
Vandal Resistance	IK10+				

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- The TV-Out function only works in 640 x 480 resolution. For TV-Out to work properly, you must set the video resolution to 1280 x 1024 or lower. If both streams are enabled, the Sub Stream must be set to 640 x 480.
- Memory card slot (local storage) is not supported in Argentina.



Vandal Proof Dome Specifications (Part 4)





		GV-VD2540-E	GV-VD5340-E
			
Camera			
Image Sensor		1/2.8" progressive scan super low lux CMOS	
Picture Elements		1920 (H) x 1080 (V)	
Minimum Illumination	Color	0.02 Lux	
	B/W	0.02 Lux	
	IR ON	0 Lux	
Shutter Speed		Auto, Manual (1/5 ~ 1/8000 sec)	
White Balance		Auto, Manual (2800K ~ 8500K)	
Gain Control		Automatic	
S/N Ratio		52 dB	
WDR Pro (with WDR sensor)		N/A	
Dynamic Range		Up to 72 dB	
Operation			
Video Compression		H.264, MJPEG	
Video Streaming		Dual streams	
Frame Rate		30 fps at 1920 x 1080	
Audio Compression		G.711, AAC (optional)	
Sensor Input		1 Input (Dry Contact)	
Alarm Output		1 Output (200mA 5V DC)	
Optical Lens			
Megapixel		Yes	
Day/Night		Yes (with removable IR-cut filter)	
Lens Type		Motorized Varifocal Lens	
Focal Length		3 ~ 9 mm	
Maximum Aperture		F/1.2	
Mount		Ø14 mm	
Image Format		1/2.7"	
Horizontal FOV		103° ~ 36°	
Operation	Focus	Auto Focus	
	Zoom	3x Optical Zoom	
	Iris	DC drive	
High Power LED		6 IR LEDs	
Max. IR Distance		25 m (82.0 ft)	
Mechanical			
Camera Angle	Pan	-90° ~ 90°	
	Tilt	0° ~ 85°	
Adjustment	Rotate	0° ~ 350°	
	Temperature Detector	Yes	
Connectors	Power	2-pin terminal block, PoE	
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector	
	Audio	1 In (3.5 mm phone jack for microphone), 1 Out (3.5 mm phone jack for speaker)	
	Digital I/O	3-pin terminal block, pitch 2.5 mm (0.1")	
	Local Storage*	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported	
TV-Out		BNC connector (640 x 480 resolution)	
LED Indicator		2 LEDs: Power, Status	
General			
Environment Temperature		-40 °C ~ 50 °C (-40 °F ~ 122 °F)	
Heat On		On (0°C / 32°F), Off (1°C / 33.8°F)	
Fan		Constantly on	
Humidity		10% to 90% (no condensation)	
Power Source		12V DC / 24V AC / PoE (IEEE 802.3at)	
Max. Power Consumption		30 W	
Regulatory		CE, FCC, RCM, RoHS compliant	
Dimensions		Ø176.5 x 118 mm (6.9" x 4.6")	
Weight		1.83 kg (4.03 lb)	
Ingress Protection		IP67	
Vandal Resistance		IK10+	

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- The TV-Out function only works in 640 x 480 resolution. For TV-Out to work properly, you must set the video resolution to 1280 x 1024 or lower. If both streams are enabled, the Sub Stream must be set to 640 x 480.
- Memory card slot (local storage) is not supported in Argentina.



Fixed Dome Specifications (Part 1)




		GV-FD220D	GV-FD320D	GV-FD1200	GV-FD1500
					
Camera					
Image Sensor		1/2.5" progressive scan CMOS		1/3" progressive scan low lux CMOS	1/3" progressive scan super low lux CMOS
Picture Elements		1920 (H) x 1080 (V)	2048 (H) x 1536 (V)	1280 (H) x 1024 (V)	1280 (H) x 1024 (V)
Minimum Illumination	Color	0.15 Lux		0.05 Lux	0.01 Lux
	B/W	0.10 Lux		0.03 Lux	0.01 Lux
	IR ON	0 Lux			
Shutter Speed		Auto, Manual (1/5 ~ 1/8000 sec)			
White Balance		Auto, Manual (2800K ~ 8500K)			
Gain Control		Automatic			
S/N Ratio		45 dB		50 dB	55 dB
WDR Pro (with WDR sensor)		N/A			
Dynamic Range		Up to 72 dB			
Operation					
Video Compression		H.264, MJPEG			
Video Streaming		Dual streams			
Frame Rate		30 fps at 1920 x 1080	20 fps at 2048 x 1536	30 fps at 1280 x 1024	30 fps at 1280 x 1024
Audio Compression		G.711, AAC (optional)			
Sensor Input		1 Input (Dry Contact)			
Alarm Output		1 Digital output (200mA 5V DC)			
Optical Lens					
Megapixel		Yes			
Day/Night		Yes (with removable IR-cut filter)			
Lens Type		Varifocal Lens			
Focal Length		3 ~ 9 mm			
Maximum Aperture		F/1.3 ± 5%		F/1.2	
Mount		Ø14 mm			
Image Format		1/3"		1/2.7"	
Horizontal FOV		82° ~ 30°	86° ~ 31°	86° ~ 32°	90° ~ 32°
Operation	Focus	Manual (w/lock)			
	Zoom	Manual (w/lock)			
	Iris	DC drive		DC drive; P-Iris (Coming)	
IR LED Quantity		10 IR LEDs			
Max. IR Distance		15 m (50 ft)			30 m (98.4 ft)
Mechanical					
Camera Angle	Pan	0° ~ 350°			
	Tilt	10° ~ 90°			
Adjustment	Rotate	0° ~ 340°			
	Temperature Detector	Yes			
Connectors	Power	2-pin terminal block, PoE			
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector			
	Audio	1 In (microphone phone jack, 3.5mm / 0.14")			
		1 Out (Stereo phone jack, 3.5mm / 0.14")			
	Digital I/O	3-pin terminal block, pitch 2.5 mm			
Local Storage*	Local Storage*	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10)			
	TV-Out	*SDXC and UHS-I card types are not supported BNC connector (640 x 480 resolution)			
LED Indicator		2 LEDs: Power, Status			
General					
Environment Temperature		0 °C ~ 50 °C / 32 °F ~ 122 °F			
Humidity		10% to 90% (no condensation)			
Power Source		12V DC / 24V AC / PoE (IEEE 802.3af)			
Max. Power Consumption		12W			
Regulatory		CE, FCC, RCM, RoHS compliant			
Dimension		Ø 155 x 110 mm (6.1" x 4.33")			
Weight		580 g (1.28 lb)			
Vandal Resistance		IK7			

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- The TV-Out function only works in 640 x 480 resolution. For TV-Out to work properly, you must set the video resolution to 1280 x 1024 or lower. If both streams are enabled, the Sub Stream must be set to 640 x 480.
- Memory card slot (local storage) is not supported in Argentina.



Fixed Dome Specifications (Part 2)






		GV-FD2400	GV-FD2500	GV-FD3400
				
Camera				
Image Sensor		1/3.2" progressive scan CMOS	1/2.8" progressive scan super low lux CMOS	1/3.2" progressive scan CMOS
Picture Elements		1920 (H) x 1080 (V)		2048 (H) x 1536 (V)
Minimum Illumination	Color	0.08 Lux	0.02 Lux	0.08 Lux
	B/W	0.05 Lux	0.02 Lux	0.05 Lux
	IR ON	0 Lux		
Shutter Speed		Auto, Manual (1/5 ~ 1/8000 sec)		
White Balance		Auto, Manual (2800K ~ 8500K)		
Gain Control		Automatic		
S/N Ratio		47 dB	52 dB	47 dB
WDR Pro (with WDR sensor)		Yes	N/A	Yes
Dynamic Range		Up to 100 dB	Up to 72 dB	Up to 100 dB
Operation				
Video Compression		H.264, MJPEG		
Video Streaming		Dual streams		
Frame Rate		30 fps at 1920 x 1080		20 fps at 2048 x 1536
Audio Compression		G.711, AAC (optional)		
Sensor Input		1 Input (Dry Contact)		
Alarm Output		1 Digital output (200mA 5V DC)		
Optical Lens				
Megapixel		Yes		
Day/Night		Yes (with removable IR-cut filter)		
Lens Type		Varifocal Lens		
Focal Length		3 ~ 9 mm		
Maximum Aperture		F/1.2		
Mount		Ø14 mm		
Image Format		1/2.7"		
Horizontal FOV		82° ~ 30°	103° ~ 36°	86° ~ 31°
Operation	Focus	Manual (w/lock)		
	Zoom	Manual (w/lock)		
	Iris	DC drive	DC drive; P-Iris (Coming)	
IR LED Quantity		10 IR LEDs		
Max. IR Distance		30 m (98.4 ft)		
Mechanical				
Camera Angle	Pan	0° ~ 350°		
	Tilt	10° ~ 90°		
	Rotate	0° ~ 340°		
Temperature Detector		Yes		
Connectors	Power	2-pin terminal block, PoE		
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector		
	Audio	1 In (microphone phone jack, 3.5mm / 0.14")		
		1 Out (Stereo phone jack, 3.5mm / 0.14")		
	Digital I/O	3-pin terminal block, pitch 2.5 mm		
Local Storage*	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported			
TV-Out		BNC connector (640 x 480 resolution)		
LED Indicator		2 LEDs: Power, Status		
General				
Environment Temperature		0 °C ~ 50 °C / 32 °F ~ 122 °F		
Humidity		10% to 90% (no condensation)		
Power Source		12V DC / 24V AC / PoE (IEEE 802.3af)		
Max. Power Consumption		12W		
Regulatory		CE, FCC, RCM, RoHS compliant		
Dimension		Ø 155 x 110 mm (6.1" x 4.33")		
Weight		580 g (1.28 lb)		
Vandal Resistance		IK7		

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- The TV-Out function only works in 640 x 480 resolution. For TV-Out to work properly, you must set the video resolution to 1280 x 1024 or lower. If both streams are enabled, the Sub Stream must be set to 640 x 480.
- Memory card slot (local storage) is not supported in Argentina.



Fixed Dome Specifications (Part 3)



	GV-FD1210	GV-FD1510	GV-FD2410	GV-FD2510	GV-FD3410
					
Camera					
Image Sensor	1/3" progressive scan low lux CMOS	1/3" progressive scan super low lux CMOS	1/3.2" progressive scan CMOS	1/2.8" progressive scan super low lux CMOS	1/3.2" progressive scan CMOS
Picture Elements	1280 (H) x 1024 (V)		1920 (H) x 1080 (V)		2048 (H) x 1536 (V)
Minimum Illumination	Color	0.05 Lux	0.01 Lux	0.08 Lux	0.02 Lux
	B/W	0.03 Lux	0.01 Lux	0.05 Lux	0.02 Lux
	IR ON	0 Lux			
Shutter Speed	Auto, Manual (1/5 ~ 1/8000 sec)				
White Balance	Auto, Manual (2800K ~ 8500K)				
Gain Control	Automatic				
S/N Ratio	50 dB	55 dB	47 dB	52 dB	47 dB
WDR Pro (with WDR sensor)	N/A		Yes	N/A	Yes
Dynamic Range	Up to 72 dB		Up to 100 dB	Up to 72 dB	Up to 100 dB
Operation					
Video Compression	H.264, MJPEG				
Video Streaming	Dual streams				
Frame Rate	30 fps at 1280 x 1024		30 fps at 1920 x 1080		20 fps at 2048 x 1536
Audio Compression	G.711, AAC (optional)				
Sensor Input	1 Input (Dry Contact)				
Alarm Output	1 Digital output (200mA 5V DC)				
Optical Lens					
Megapixel	Yes				
Day/Night	Yes (with removable IR-cut filter)				
Lens Type	Motorized Varifocal Lens				
Focal Length	3 ~ 9 mm				
Maximum Aperture	F/1.2				
Mount	Ø14 mm				
Image Format	1/2.7"				
Horizontal FOV	86° ~ 32°	90° ~ 32°	82° ~ 30°	103° ~ 36°	86° ~ 31°
Operation	Focus	Auto Focus			
	Zoom	3X Optical Zoom			
	Iris	DC drive	DC drive; P-Iris (Coming)	DC drive	P-Iris
IR LED Quantity	10 IR LEDs				
Max. IR Distance	15 m (50 ft)	30 m (98.4 ft)			
Mechanical					
Camera Angle Adjustment	Pan	0° ~ 350°			
	Tilt	10° ~ 90°			
	Rotate	0° ~ 340°			
Temperature Detector	Yes				
Connectors	Power	2-pin terminal block, PoE			
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector			
	Audio	1 In (microphone phone jack, 3.5mm / 0.14") 1 Out (Stereo phone jack, 3.5mm / 0.14")			
	Digital I/O	3-pin terminal block, pitch 2.5 mm			
	Local Storage*	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported			
TV-Out	BNC connector (640 x 480 resolution)				
LED Indicator	2 LEDs: Power, Status				
General					
Environment Temperature	0 °C ~ 50 °C / 32 °F ~ 122 °F				
Humidity	10% to 90% (no condensation)				
Power Source	12V DC / 24V AC / PoE (IEEE 802.3af)				
Max. Power Consumption	12W				
Regulatory	CE, FCC, RCM, RoHS compliant				
Dimension	Ø 155 x 110 mm (6.1" x 4.33")				
Weight	580 g (1.28 lb)				
Vandal Resistance	IK7				

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- The TV-Out function only works in 640 x 480 resolution. For TV-Out to work properly, you must set the video resolution to 1280 x 1024 or lower. If both streams are enabled, the Sub Stream must be set to 640 x 480.
- Memory card slot (local storage) is not supported in Argentina.



Cube Camera Specifications





		GV-CB120	GV-CB220
			
Camera			
Image Sensor		1/2.5" progressive scan CMOS	
Picture Elements		1280 (H) x 1024 (V)	1920 (H) x 1080 (V)
Minimum Illumination	Color	0.15 Lux	
	B/W	0.10 Lux	
	IR ON	N/A	
Shutter Speed		Auto, Manual (1/5 ~ 1/8000 sec)	
White Balance		Auto, Manual (2800K ~ 8500K)	
Gain Control		Automatic	
S/N Ratio		45 dB	
Dynamic Range		Up to 72 dB	
Operation			
Video Compression		H.264, MJPEG	
Video Streaming		Dual streams	
Frame Rate		30 fps at 1280 x 1024	30 fps at 1920 x 1080
Audio Compression		G.711, AAC (optional)	
Optical Lens			
Megapixel		Yes	
Day/Night		Yes (electronic)	
Lens Type		Fixed Lens	
Focal Length		3.35 mm	
Maximum Aperture		F/2.4	
Mount		M12 mm	
Image Format		1/3"	
Horizontal FOV		67°	77°
Operation	Focus	Fixed	
	Zoom		
	Iris		
Mechanical			
Connectors	Power	DC Jack	
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector	
	Audio	built-in microphone and speaker	
	Local Storage*	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported	
LED Indicator		2 LEDs: Status, LAN	
Wireless LAN		No	
General			
Environment Temperature		0 °C ~ 50 °C (32 °F ~ 122 °F)	
Humidity		10% to 90% (no condensation)	
Power Source		5V DC	
Max. Power Consumption		3.2 W	
Regulatory		CE, FCC, RCM, RoHS compliant	
Dimensions		60 x 84.8 x 39 mm (2.36" x 3.34" x 1.54")	
Weight		80 g (0.18 lb)	

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- Be sure to use the supplied power adapter to power up the camera. To use your own power cable, make sure you look up the power source value indicated at the camera's back panel.
- Memory card slot (local storage) is not supported in Argentina.**



Advanced Cube Camera Specifications




		GV-CA120	GV-CA220	GV-CAW120	GV-CAW220
					
Camera					
Image Sensor		1/2.5" progressive scan CMOS			
Picture Elements		1280 (H) x 1024 (V)	1920 (H) x 1080 (V)	1280 (H) x 1024 (V)	1920 (H) x 1080 (V)
Minimum Illumination	Color	0.15 Lux			
	B/W	0.10 Lux			
	IR ON	N/A			
	White Illumination LED	0 Lux			
Shutter Speed		Auto, Manual (1/5 ~ 1/8000 sec)			
White Balance		Auto, Manual (2800K ~ 8500K)			
Gain Control		Automatic			
S/N Ratio		45 dB			
Dynamic Range		Up to 72 dB			
Operation					
Video Compression		H.264, MJPEG			
Video Streaming		Dual streams			
Frame Rate		30 fps at 1280 x 1024	30 fps at 1920 x 1080	30 fps at 1280 x 1024	30 fps at 1920 x 1080
Audio Compression		G.711, AAC (optional)			
Optical Lens					
Megapixel		Yes			
Day/Night		Yes (electronic)			
Lens Type		Fixed Lens			
Focal Length		3.35 mm			
Maximum Aperture		F/2.4			
Mount		M12 mm			
Image Format		1/3"			
Horizontal FOV		67°	77°	67°	77°
Operation	Focus	Fixed			
	Zoom	Fixed			
	Iris	Fixed			
Mechanical					
Connectors	Power	DC Jack / PoE (IEEE 802.3af Class 3, only for GV-CA120/220)			
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector			
	Audio	built-in microphone and speaker			
	Local Storage*	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported			
LED Indicator		4 LEDs: Status x 3, LAN/WiFi			
PIR Sensor		Built-in			
White Illumination LED		Yes			
Max. PIR / White Illumination LED Distance		5 m (16.4 ft)			
General					
Environment Temperature		0 °C ~ 50 °C (32 °F ~ 122 °F)			
Humidity		10% to 90% (no condensation)			
Power Source		5V DC and PoE		5V DC	
Max. Power Consumption		7 W		6 W	
Regulatory		CE, FCC, RCM, RoHS compliant			
Dimensions (LxWxH)		65.8 x 99.8 x 39 mm (2.59" x 3.92" x 1.54")			
Weight		100 g (0.2 lb)			

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- For GV-CAW120 / CAW220, the signal range and data throughput may vary depending on the network conditions and environmental factors.
- Memory card slot (local storage) is not supported in Argentina.



Mini Fixed Dome Specifications (Part 1)






		GV-MFD120	GV-MFD130	GV-MFD320
				
Camera		1/3" progressive scan low lux CMOS		1/2.5" progressive scan CMOS
Image Sensor		1280 (H) x 1024 (V)		2048 (H) x 1536 (V)
Picture Elements		1280 (H) x 1024 (V)		2048 (H) x 1536 (V)
Minimum Illumination	Color	0.05 Lux		0.15 Lux
	B/W	0.03 Lux		0.10 Lux
	IR ON	N/A		
Shutter Speed		Auto, Manual (1/5 ~ 1/8000 sec)		
White Balance		Auto, Manual (2800K ~ 8500K)		
Gain Control		Automatic		
S/N Ratio		50 dB	45 dB	
Dynamic Range		Up to 72 dB		
Operation				
Video Compression		H.264, MJPEG		
Video Streaming		Dual streams		
Frame Rate		30 fps at 1280 x 1024		20 fps at 2048 x 1536
Audio Compression		G.711, AAC (optional)		
Optical Lens				
Megapixel		Yes		
Day/Night		Yes (electronic)		
Lens Type		Fixed Lens		
Focal Length		4.05 mm	2.54 mm	
Maximum Aperture		F/1.5	F/2.8	
Mount		M12, Pitch 0.5 mm		
Image Format		1/3"	1/2.5"	
Horizontal FOV		67°	85°	110°
Operation	Focus	Fixed		
	Zoom	Fixed		
	Iris	Fixed		
Mechanical				
Camera Angle Adjustment	Pan	-45° ~ 45°		
	Tilt	0° ~ 90°		
Temperature Detector		Yes		
Connectors	Power	2-pin terminal block, PoE		
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector		
	Audio	built-in microphone		
	USB	N/A		
Local Storage*		Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported		
LED Indicator		4 LEDs: Link, ACT, Power, Status		
General				
Environment Temperature		0 °C ~ 50 °C (32 °F ~ 122 °F)		
Humidity		10% to 90% (no condensation)		
Power Source		12V DC / PoE (IEEE 802.3af)		
Max. Power Consumption		4.5 W	5.5 W	
Regulatory		CE, FCC, RCM, RoHS compliant		
Dimensions	Camera Body	ø 106 x 55.6 mm (4.2" x 2.2")		
	Cable Length	1 m (3.28 ft)		
	Cable Diameter	ø 8 mm (0.31")		
	Max. Connector Diameter	ø 28.5 mm (1.12")		
Weight		275 g (0.61 lb)	280 g (0.62 lb)	

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- Memory card slot (local storage) is not supported in Argentina.
- Mind the following limitations and requirements for the mini USB port:
 - The USB hard drive must be of 2.5" or 3.5", version 2.0 or above
 - The USB hard drive's storage capacity must not exceed 2TB
 - USB flash drives and USB hubs are not supported
 - External power supply is required for the USB hard drive
 - To connect a GV-WiFi Adapter, make sure it is connected before the camera is powered on.



Mini Fixed Dome Specifications (Part 2)




		GV-MFD1501 Series		GV-MFD2401 Series		GV-MFD2501 Series		GV-MFD3401 Series		GV-MFD5301 Series			
													
Camera													
Image Sensor		1/3" progressive scan super low lux CMOS		1/3.2" progressive scan CMOS		1/2.8" progressive scan super low lux CMOS		1/3.2" progressive scan CMOS		1/2.5" progressive scan CMOS			
Picture Elements		1280 (H) x 1024 (V)		1920 (H) x 1080 (V)		1920 (H) x 1080 (V)		2048 (H) x 1536 (V)		2560 (H) x 1920 (V)			
Minimum Illumination	Color	0.01 Lux		0.08 Lux		0.02 Lux		0.08 Lux		0.15 Lux			
	B/W	0.01 Lux		0.05 Lux		0.02 Lux		0.05 Lux		0.10 Lux			
										N/A			
Shutter Speed		Auto, Manual (1/5 ~ 1/8000 sec)											
White Balance		Auto, Manual (2800K ~ 8500K)											
Gain Control		Automatic											
S/N Ratio		55 dB				52 dB				55 dB			
WDR Pro (with WDR Sensor)		N/A		Yes		N/A		Yes		N/A			
Dynamic Range		Up to 72 dB		Up to 100 dB		Up to 72 dB		Up to 100 dB		Up to 72 dB			
Operation													
Video Compression		H.264, MJPEG											
Video Streaming		Dual streams											
Frame Rate		30 fps at 1280 x 1024		30 fps at 1920 x 1080				20 fps at 2048 x 1536		10 fps at 2560 x 1920			
Audio Compression		G.711, AAC (optional)											
Optical Lens													
Megapixel		Yes											
Day/Night		Yes (electronic)											
Lens Type		Fixed Lens											
Focal Length	MFD1501-0F	2.8 mm	MFD2401-0F	2.8 mm	MFD2501-0F	2.8 mm	MFD3401-0F	2.8 mm	MFD5301-0F	2.8 mm			
	MFD1501-1F	4 mm	MFD2401-2F	8 mm	MFD2501-1F	4 mm	MFD3401-2F	8 mm	MFD5301-2F	8 mm			
	MFD1501-2F	8 mm	MFD2401-3F	12 mm	MFD2501-2F	8 mm	MFD3401-3F	12 mm	MFD5301-3F	12 mm			
	MFD1501-3F	12 mm	MFD2401-4F	2.1 mm	MFD2501-3F	12 mm	MFD3401-5F	3.8 mm	MFD5301-5F	3.8 mm			
	MFD1501-4F	2.1 mm	MFD2401-5F	3.8 mm	MFD2501-5F	3.8 mm	MFD3401-6F	2.3 mm					
MFD1501-5F	3.8 mm	MFD2501-6F			2.3 mm	MFD3401-6F	2.3 mm	MFD5301-5F	3.8 mm				
Maximum Aperture	MFD1501-0F	F/2.0	MFD2401-0F	F/2.0	MFD2501-0F	F/2.0	MFD3401-0F	F/2.0	MFD5301-0F	F/2.0			
	MFD1501-1F	F/1.5	MFD2401-2F	F/1.6	MFD2501-1F	F/1.5	MFD3401-2F	F/1.6	MFD5301-2F	F/1.6			
	MFD1501-2F	F/1.6	MFD2401-3F	F/1.6	MFD2501-2F	F/1.6	MFD3401-3F	F/1.6	MFD5301-3F	F/1.6			
	MFD1501-3F	F/1.6	MFD2401-4F	F/1.8	MFD2501-3F	F/1.6	MFD3401-5F	F/1.8	MFD5301-5F	F/1.8			
	MFD1501-4F	F/1.8	MFD2401-5F	F/1.8	MFD2501-5F	F/1.8	MFD3401-6F	F/2.2					
MFD1501-5F	F/1.8	MFD2501-6F			F/2.2	MFD3401-6F	F/2.2	MFD5301-5F	F/1.8				
Mount		M12, Pitch 0.5 mm											
Image Format		1/3"											
Horizontal FOV	MFD1501-0F	87°	MFD2401-0F	79°	MFD2501-0F	99°	MFD3401-0F	80°	MFD5301-0F	103°			
	MFD1501-1F	67°	MFD2401-2F	31°	MFD2501-1F	72°	MFD3401-2F	33°	MFD5301-2F	41°			
	MFD1501-2F	35°	MFD2401-3F	20°	MFD2501-2F	38°	MFD3401-3F	21°	MFD5301-3F	26°			
	MFD1501-3F	22°	MFD2401-4F	112°	MFD2501-3F	25°	MFD3401-5F	63°	MFD5301-5F	76°			
	MFD1501-4F	124°	MFD2401-5F	60°	MFD2501-5F	72°	MFD3401-6F	105°					
	MFD1501-5F	64°			MFD2501-6F	122°	MFD3401-6F	105°	MFD5301-5F	76°			
Operation	Focus	Fixed											
	Zoom	Fixed											
	Iris	Fixed											
Mechanical													
Camera Angle Adjustment	Pan	-45° ~ 45°											
	Tilt	0° ~ 90°											
Temperature Detector		Yes											
Connectors	Power	PoE, 2-pin terminal block											
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector											
	Audio	1 In (Built-in microphone), 1 Out (RCA female for speaker)											
	USB	GV-WiFi adapter or USB hard drive											
	Local Storage*	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported											
LED Indicator		4 LEDs: Link, ACT, Power, Status											
General													
Environment Temperature		0 °C ~ 50 °C (32 °F ~ 122 °F)											
Humidity		10% to 90% (no condensation)											
Power Source		DC 5V, PoE (IEEE 802.3af)											
Max. Power Consumption		6 W											
Regulatory		CE, FCC, RCM, RoHS compliant											
Dimensions		ø106 x 53.9 mm (4.2" x 2.1")											
Weight		280 g (0.62 lb)											



Note:

1. Product design and specifications are subject to change without notice.
2. The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
3. **Memory card slot (local storage) is not supported in Argentina.**
4. Mind the following limitations and requirements for the mini USB port:
 - The USB hard drive must be of 2.5" or 3.5", version 2.0 or above
 - The USB hard drive's storage capacity must not exceed 2TB
 - USB flash drives and USB hubs are not supported
 - External power supply is required for the USB hard drive
 - To connect a GV-WiFi Adapter, make sure it is connected before the camera is powered on.

Mini Fixed Rugged Dome Specifications (Part 1)




		GV-MDR220	GV-MDR320	GV-MDR520
				
Camera				
Image Sensor		1/2.5" progressive scan CMOS		
Picture Elements		1920 (H) x 1080 (V)	2048 (H) x 1536 (V)	2560 (H) x 1920 (V)
Minimum Illumination	Color	0.15 Lux		
	B/W	0.10 Lux		
	IR ON	N/A		
Shutter Speed		Auto, Manual (1/5 ~ 1/8000 sec)		
White Balance		Auto, Manual (2800K ~ 8500K)		
Gain Control		Automatic		
S/N Ratio		45 dB		
WDR Pro (with WDR sensor)		N/A		
Dynamic Range		Up to 72 dB		
Operation				
Video Compression		H.264, MJPEG		
Video Streaming		Dual streams		
Frame Rate		30 fps at 1920 x 1080	20 fps at 2048 x 1536	10 fps at 2560 x 1920
Audio Compression		G.711, AAC (optional)		
Optical Lens				
Megapixel		Yes		
Day/Night		Yes (electronic)		
Lens Type		Fixed Lens		
Focal Length		2.54 mm		
Maximum Aperture		F/2.8		
Mount		M12, Pitch 0.5 mm		
Image Format		1/2.5"		
Horizontal FOV		101°	110°	138°
Operation	Focus	Fixed		
	Zoom	Fixed		
	Iris	Fixed		
Mechanical				
Camera Angle Adjustment	Pan	-45° ~ 45°		
	Tilt	0° ~ 90°		
	Rotate	0° ~ 360°		
Temperature Detector		Yes		
Connectors	Power	PoE		
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector		
	Audio	built-in microphone		
	Local Storage	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported		
LED Indicator		3 LEDs: Link, Power, Status		
General				
Environment Temperature		-30 °C ~ 50 °C (-22 °F ~ 122 °F)		
Humidity		10% to 90% (no condensation)		
Power Source		PoE		
Max. Power Consumption		3.4 W		3.6 W
Regulatory		CE, FCC, RCM, RoHS compliant		
Dimensions	Camera Body	ø 115 x 59.2 mm (4.5" x 2.3")		
	Cable Length	1.054 m (41.5")		
	Cable Diameter	ø 6.2 mm (0.24")		
	Max. Connector Diameter	ø 30 mm (1.18")		
Weight		568g (1.3 lb)		
Ingress Protection		IP67		
Vandal Resistance		IK10 for metal casing		

Note:

1. Product design and specifications are subject to change without notice.
2. The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
3. **Memory card slot (local storage) is not supported in Argentina.**



Mini Fixed Rugged Dome Specifications (Part 2)




	GV-MDR1500 Series		GV-MDR3400 Series		GV-MDR5300 Series	
						
Camera						
Image Sensor	1/3" progressive scan super low lux CMOS		1/3.2" progressive scan CMOS		1/2.5" progressive scan CMOS	
Picture Elements	1280 (H) x 1024 (V)		2048 (H) x 1536 (V)		2560 (H) x 1920 (V)	
Minimum Illumination	Color	0.01 Lux	0.08 Lux		0.15 Lux	
	B/W	0.01 Lux	0.05 Lux		0.10 Lux	
	IR ON		N/A			
Shutter Speed			Auto, Manual (1/5 ~ 1/8000 sec)			
White Balance			Auto, Manual (2800K ~ 8500K)			
Gain Control			Automatic			
S/N Ratio	55 dB		47 dB		45 dB	
WDR Pro (with WDR Sensor)	N/A		Yes		N/A	
Dynamic Range	Up to 72 dB		Up to 100 dB		Up to 72 dB	
Operation						
Video Compression			H.264, MJPEG			
Video Streaming			Dual streams			
Frame Rate	30 fps at 1280 x 1024		20 fps at 2048 x 1536		10 fps at 2560 x 1920	
Audio Compression			G.711, AAC (optional)			
Optical Lens						
Megapixel			Yes			
Day/Night			Yes (electronic)			
Lens Type			Fixed Lens			
Focal Length	MDR1500-1F	2.8 mm	MDR3400-1F	2.8 mm	MDR5300-1F	2.8 mm
	MDR1500-2F	3.8 mm	MDR3400-2F	3.8 mm	MDR5300-2F	3.8 mm
Maximum Aperture	MDR1500-1F	F/2.0	MDR3400-1F	F/2.0	MDR5300-1F	F/2.0
	MDR1500-2F	F/1.8	MDR3400-2F	F/1.8	MDR5300-2F	F/1.8
Mount			M12, Pitch 0.5 mm			
Image Format			1/3"			
Horizontal FOV	MDR1500-1F	88°	MDR3400-1F	85°	MDR5300-1F	104°
	MDR1500-2F	64°	MDR3400-2F	63°	MDR5300-2F	76°
Operation	Focus			Fixed		
	Zoom					
	Iris					
Mechanical						
Camera Angle Adjustment	Pan			-45° ~ 45°		
	Tilt			0° ~ 90°		
	Rotate			0° ~ 360°		
Temperature Detector			Yes			
Connectors	Power			PoE		
	Ethernet			Ethernet (10/100 Base-T), RJ-45 connector		
	Audio			built-in microphone		
	Local Storage			Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported		
LED Indicator			3 LEDs: Link, Power, Status			
General						
Environment Temperature			-30 °C ~ 50 °C (-22 °F ~ 122 °F)			
Humidity			10% to 90% (no condensation)			
Power Source			PoE			
Max. Power Consumption	3.47 W		4.28 W		3.81 W	
Regulatory						
Dimensions	Camera Body			ø 115 x 59.2 mm (4.5" x 2.3")		
	Cable Length			1.054 m (41.5")		
	Cable Diameter			ø 6.2 mm (0.24")		
	Connector Diameter			M12: ø 14.7 mm (0.58") Waterproof: ø 27 mm (1.06") Non-waterproof (Smaller): 16.8 x 13.8 mm (0.66" x 0.54")		
	Weight			568g (1.3 lb)		
Ingress Protection			IP67			
Vandal Resistance			IK10 for metal casing			

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- Memory card slot (local storage) is not supported in Argentina.



Target Series Specifications (Part 1)





		GV-EBX1100 Series		GV-EBL1100 Series		GV-EBL2100 Series	
							
Camera							
Image Sensor		1/3" progressive scan low lux CMOS		1/3" progressive scan low lux CMOS		1/2.8" progressive scan low lux CMOS	
Picture Elements		1280 (H) x 1024 (V)		1280 (H) x 1024 (V)		1920 (H) x 1080 (V)	
Minimum Illumination	Color	0.05 Lux		0.05 Lux		0.07 Lux	
	B/W	0.03 Lux		0.03 Lux		0.04 Lux	
	IR ON			0 Lux			
Shutter Speed				Auto, Manual (1/5 ~ 1/8000 sec)			
White Balance				Auto, Manual (2800K ~ 8500K)			
Gain Control				Automatic			
S/N Ratio		50 dB		50 dB		48 dB	
Dynamic Range				Up to 72 dB			
Operation							
Video Compression				H.264, MJPEG			
Video Streaming				Dual streams			
Frame Rate		30 fps at 1280 x 1024				30 fps at 1920 x 1080	
Audio Compression		G.711, AAC (optional)				N/A	
Optical Lens							
Megapixel				Yes			
Day/Night				Yes (with removable IR-cut filter)			
Lens Type				Fixed			
Focal Length	GV-EBX1100-0F	2.8 mm	GV-EBL1100-1F	6 mm	GV-EBL2100-1F	6 mm	
	GV-EBX1100-2F	3.8 mm	GV-EBL1100-2F	3.8 mm	GV-EBL2100-2F	3.8 mm	
Maximum Aperture	GV-EBX1100-0F	F/2.0	GV-EBL1100-1F	F/1.8	GV-EBL2100-1F	F/1.8	
	GV-EBX1100-2F	F/1.8	GV-EBL1100-2F		GV-EBL2100-2F		
Mount				M12, Pitch 0.5 mm			
Image Format				1/2.7"			
Horizontal FOV	GV-EBX1100-0F	93°	GV-EBL1100-1F	44°	GV-EBL2100-1F	51°	
	GV-EBX1100-2F	64°	GV-EBL1100-2F	64°	GV-EBL2100-2F	72°	
Operation	Focus			Fixed			
	Zoom						
	Iris						
IR LED Quantity		8 IR LEDs		24 IR LEDs			
Max. IR Distance		15 m (50 ft)		30 m (98.4 ft)			
Mechanical							
Camera Angle Adjustment	Pan	N/A		N/A			
	Tilt						
Connectors	Power			2-pin terminal block, PoE			
	Ethernet			Ethernet (10/100 Base-T), RJ-45 cable			
	Audio	1 In (built-in microphone)				N/A	
LED Indicator		2 LEDs: Power, Status		4 LEDs: Link, ACT, Power, Status * Inside camera, not visible from outside			
General							
Environment Temperature		0°C ~ 50°C (32°F ~ 122°F)		Start-up	-20°C ~ 50°C (-4°F ~ 122°F)		
				Operation	-30°C ~ 50°C (-22°F ~ 122°F)		
Humidity				10% to 90% (no condensation)			
Power Source				12V DC / PoE (IEEE 802.3af)			
Max. Power Consumption		5.36 W		7.8 W			
Regulatory				CE, FCC, RCM, RoHS compliant			
Dimensions (L X W X H)		95 x 45 x 40 mm (3.7" x 1.8" x 1.6")		115 x 76 x 73 mm (4.5" x 3.0" x 2.9")			
Weight		120 g (0.26 lb)		547 g (1.20 lb)			
Ingress Protection		N/A		IP67			
Vandal Resistance		N/A		IK10 for metal casing			

Note:

1. Product design and specifications are subject to change without notice.
2. The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).



Target Series Specifications (Part 2)






		GV-EFD1100 Series		GV-EFD2100 Series		GV-EDR1100 Series		GV-EDR2100 Series	
									
Camera									
Image Sensor		1/3" progressive scan low lux CMOS		1/2.8" progressive scan low lux CMOS		1/3" progressive scan low lux CMOS		1/2.8" progressive scan low lux CMOS	
Picture Elements		1280 (H) x 1024 (V)		1920 (H) x 1080 (V)		1280 (H) x 1024 (V)		1920 (H) x 1080 (V)	
Minimum Illumination	Color	0.05 Lux		0.07 Lux		0.05 Lux		0.07 Lux	
	B/W	0.03 Lux		0.04 Lux		0.03 Lux		0.04 Lux	
	IR ON	0 Lux							
Shutter Speed		Auto, Manual (1/5 ~ 1/8000 sec)							
White Balance		Auto, Manual (2800K ~ 8500K)							
Gain Control		Automatic							
S/N Ratio		50 dB		48 dB		50 dB		48 dB	
Dynamic Range		Up to 72 dB							
Operation									
Video Compression		H.264, MJPEG							
Video Streaming		Dual streams							
Frame Rate		30 fps at 1280 x 1024		30 fps at 1920 x 1080		30 fps at 1280 x 1024		30 fps at 1920 x 1080	
Audio Compression		G.711, AAC (optional)				N/A			
Optical Lens									
Megapixel		Yes							
Day/Night		Yes (with removable IR-cut filter)							
Lens Type		Fixed							
Focal Length	GV-EFD1100-0F	2.8 mm	GV-EFD2100-0F	2.8 mm	GV-EDR1100-0F	2.8 mm	GV-EDR2100-0F	2.8 mm	
	GV-EFD1100-2F	3.8 mm	GV-EFD2100-2F	3.8 mm	GV-EDR1100-2F	3.8 mm	GV-EDR2100-2F	3.8 mm	
Maximum Aperture	GV-EFD1100-0F	F/2.0	GV-EFD2100-0F	F/2.0	GV-EDR1100-0F	F/2.0	GV-EDR2100-0F	F/2.0	
	GV-EFD1100-2F	F/1.8	GV-EFD2100-2F	F/1.8	GV-EDR1100-2F	F/1.8	GV-EDR2100-2F	F/1.8	
Mount		M12, Pitch 0.5 mm							
Image Format		1/2.7"							
Horizontal FOV	GV-EFD1100-0F	93°	GV-EFD2100-0F	99°	GV-EDR1100-0F	93°	GV-EDR2100-0F	99°	
	GV-EFD1100-2F	64°	GV-EFD2100-2F	72°	GV-EDR1100-2F	64°	GV-EDR2100-2F	72°	
Operation	Focus	Fixed							
	Zoom	Fixed							
	Iris	Fixed							
IR LED Quantity		12 IR LEDs							
Max. IR Distance		15 m (50 ft)							
Mechanical									
Camera Angle Adjustment	Pan	-45° ~ 45°							
	Tilt	0° ~ 63°							
Connectors	Power	2-pin terminal block, PoE							
	Ethernet	Ethernet (10/100 Base-T), RJ-45 cable							
	Audio	1 In (built-in microphone)				N/A			
LED Indicator		4 LEDs: Link, ACT, Power, Status				4 LEDs: Link, ACT, Power, Status			
General									
Environment Temperature		0°C ~ 45°C (32°F ~ 113°F)				Start-up	-20°C ~ 50°C (-4°F ~ 122°F)		
						Operation	-30°C ~ 50°C (-22°F ~ 122°F)		
Humidity		10% to 90% (no condensation)							
Power Source		12V DC / PoE (IEEE 802.3af)							
Max. Power Consumption		5.8 W							
Regulatory		CE, FCC, RCM, RoHS compliant							
Dimensions (L X W X H)		ø 100 x 60 mm (3.9" x 2.4")				ø 114 x 62.8 mm (4.49" x 2.47")			
Weight		148 g (0.33 lb)				600 g (1.32 lb)			
Ingress Protection		N/A				IP67			
Vandal Resistance		N/A				IK10 for metal casing			

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).



PT and PTZ Camera Specifications






		GV-PT130D	GV-PT220D	GV-PT320D	GV-PTZ010D-N	GV-PTZ010D-P
						
Camera						
Image Sensor		1/2.5" progressive scan CMOS			1/4" CCD image sensor	
Picture Elements		1280 (H) x 1024 (V)	1920 (H) x 1080 (V)	2048 (H) x 1536 (V)	704 (H) x 480 (V)	704 (H) x 576 (V)
Minimum Illumination	Color	0.15 Lux			2.5 Lux (50 IRE, F/1.8)	
	B/W	0.10 Lux			0.07 Lux (50 IRE, F/1.8)	
	IR ON	0 Lux			N/A	
Shutter Speed		Automatic, Manual (1/5 ~ 1/8000 sec)			Auto, Manual (1/60 ~ 1/120,000 sec) Auto, Manual (1/50 ~ 1/120,000 sec)	
White Balance		Auto, Manual (2800K ~ 8500K)			Auto, Manual (3200K ~ 9600K)	
Gain Control		Automatic			Automatic	
BLC		Yes			Yes	
Dynamic Range		Up to 72 dB			N/A	
Operation						
Video Compression		H.264, MJPEG			H.264, MPEG4, MJPEG	
Video Streaming		Dual streams				
Frame Rate		30 fps at 1280 x 1024,	30 fps at 1920 x 1080	20 fps at 2048 x 1536	30 fps at 704 x 480	25 fps at 704 x 576
Audio Compression		G.711, AAC (optional)				
Sensor Input		1 Input (Dry Contact)				
Alarm Output		1 Digital output (200mA 5V DC)				
Optical Lens						
Megapixel		Yes			No	
Day/Night		Yes (with removable IR-cut filter)			Yes (electronic)	
Focal Length		4.0 mm			4.2 ~ 42 mm	
Maximum Aperture		F/1.5			F/1.8 ~ 2.9	
Mount		M12, Pitch 0.5 mm			No	
Image Format		1/2.5"			1/4"	
Horizontal FOV		49°	58°	62°	N/A	
Operation	Focus	Manual (w/lock)			Auto Focus	
	Zoom	Fixed			100X (10X Optical, 10X Digital)	
	Iris	Fixed			Fixed	
IR LED Quantity		10 IR LEDs			N/A	
Max. IR Distance		15 m (50 ft)			N/A	
Mechanical						
Camera Angle		-175° ~ 175°				
Adjustment		-45° ~ 90°				
Temperature Detector		Yes				
Connectors	Power	2-pin terminal block, PoE				
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector				
	Audio	1 In (built-in microphone or external microphone) 1 Out (Stereo phone jack, 3.5 mm / 0.14")				
	Digital I/O	3-pin terminal block, pitch 2.5 mm / 0.1"				
	Local Storage	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported				
LED Indicator		2 LEDs: Power, Status				
General						
Environment Temperature		0 °C ~ 50 °C (32 °F ~ 122 °F)				
Humidity		10% to 90% (no condensation)				
Power Source		12V DC / 24V AC / PoE (IEEE 802.3af)				
Max. Power Consumption		12.5 W				
Regulatory		CE, FCC, RCM, RoHS compliant				
Dimensions	With Base	167.75 x 166.78 x 135.2 mm (6.6" x 6.7" x 5.32")				
	Without Base	124.55 x 122.73 x 133.3 mm (4.9" x 4.83" x 5.25")				
Weight		440 g (0.97 lb)			490 g (1.08 lb)	

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- Memory card slot (local storage) is not supported in Argentina.



Fisheye Camera Specifications (Part 1)



	GV-FE420 (Indoor)	GV-FE421 (Indoor)	GV-FE520 (Indoor)	GV-FE521 (Indoor)	GV-FER521 (Outdoor)	
						
Camera						
Image Sensor	1/2.5" progressive scan CMOS					
Picture Elements	2048 (H) x 1944 (V)		2560 (H) x 1920 (V)			
Minimum Illumination	Color	0.15 Lux				
	B/W	0.10 Lux				
	IR ON	N/A				
Shutter Speed	Auto, Manual (1/5 ~ 1/8000sec)					
White Balance	Auto, Manual (2800K ~ 8500K)					
Gain Control	Automatic					
S/N Ratio	45 dB					
Dynamic Range	Up to 72 dB					
Operation						
Video Compression	H.264, MJPEG					
Video Streaming	Single Stream from H.264 or MJPEG					
Frame Rate	15 fps at 2048 x 1944		10 fps at 2560 x 1920 15 fps at 2048 x 1944			
Audio Compression	G.711, AAC (optional)					
Sensor Input	1 Input (Dry Contact)				No	
Alarm Output	1 Digital output (200mA 5V DC)				No	
Optical Lens						
Megapixel	Yes					
Day/Night	Yes (electronic)					
Focal Length	1.05 mm		1.6 mm			
Maximum Aperture	F/2.8		F/2			
Mount	M12, Pitch 0.5 mm / 0.02"					
Image Format	1/2"		4.7 mm (Image Circle)			
Horizontal FOV	180°					
Operation	Focus	Fixed				
	Zoom					
	Iris					
Mechanical						
Temperature Detector	Yes					
Connectors	Power	Terminal block (2 pin), PoE				
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector				
	Audio	built-in microphone and speaker				
	Digital I/O	I/O Wire				No
	Local Storage	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported				
General						
Environment Temperature	0 °C ~ 50 °C (32 °F ~ 122 °F)				-30 °C ~ 50 °C / -22 °F ~ 122 °F	
Humidity	10% to 90% (no condensation)					
Power Source	12V DC / 24V AC / PoE (IEEE 802.3af)				PoE (IEEE 802.3af)	
Max. Power Consumption	5 W					
Regulatory	CE, FCC, RCM, RoHS compliant					
Dimensions	Camera Body	Hard-Ceiling Mount	ø 160 x 47.66 mm (6.30" x 1.88")		ø 160 x 44.9 mm (6.30" x 1.77")	ø 160 x 46.4 mm (6.30" x 1.83")
		In-Ceiling Mount	ø 164 x 47.66 mm (6.46" x 1.88")		ø 164 x 44.9 mm (6.46" x 1.77")	ø 164 x 46.4 mm (6.46" x 1.83")
	Cable Length	1 m (3.28 ft)				
	Cable Diameter	ø 8 mm (0.31")				
Max. Connector Diameter	ø 28.5 (1.12")					
Weight	650 g (1.43 lb)				480 g (1.06 lb)	
Ingress Protection	No				IP66	
Vandal Resistance	No				IK10 for metal casing	

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- Memory card slot (local storage) is not supported in Argentina.



Fisheye Camera Specifications (Part 2)




		GV-FE2301 (Indoor)	GV-FE4301 (Indoor)
			
Camera			
Image Sensor		1/2.5" progressive scan CMOS	
Picture Elements		1440 (H) x 1376 (V)	2048 (H) x 1944 (V)
Minimum Illumination	Color	0.15 Lux	
	B/W	0.10 Lux	
	IR ON	N/A	
Shutter Speed		Auto, Manual (1/5 ~ 1/8000sec)	
White Balance		Auto, Manual (2800K ~ 8500K)	
Gain Control		Automatic	
S/N Ratio		45 dB	
Dynamic Range		Up to 72 dB	
Operation			
Video Compression		H.264, MJPEG	
Video Streaming		Single Stream from H.264 or MJPEG	
Frame Rate		15 fps at 1440 x 1376	15 fps at 2048 x 1944
Audio Compression		G.711, AAC (optional)	
Sensor Input		1 Input (Dry Contact)	
Alarm Output		1 Digital output (200mA 5V DC)	
Optical Lens			
Megapixel		Yes	
Day/Night		Yes (electronic)	
Focal Length		1.05 mm	
Maximum Aperture		F/2.8	
Mount		M12, Pitch 0.5 mm / 0.02 in	
Image Format		1/2"	
Horizontal FOV		180°	
Operation	Focus	Fixed	
	Zoom		
	Iris		
Mechanical			
Temperature Detector		Yes	
Connectors	Power	Terminal block (2 pin), PoE	
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector	
	Audio	built-in microphone and speaker	
	Digital I/O	I/O Wire	
	Local Storage	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported	
General			
Environment Temperature		0 °C ~ 50 °C (32 °F ~ 122 °F)	
Humidity		10% to 90% (no condensation)	
Power Source		12V DC / 24V AC / PoE (IEEE 802.3af)	
Max. Power Consumption		5 W	
Regulatory		CE, FCC, RCM, RoHS compliant	
Dimensions	Camera Body	Hard-Ceiling Mount	ø 160 x 47.66 mm (6.30" x 1.88")
		In-Ceiling Mount	ø 164 x 47.66 mm (6.46" x 1.88")
	Cable Length		1 m (3.28 ft)
	Cable Diameter		ø 8 mm (0.31")
	Max. Connector Diameter		ø 28.5 (1.12")
Weight		650 g (1.43 lb)	

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- Memory card slot (local storage) is not supported in Argentina.



Fisheye Camera Specifications (Part 3)



			GV-FE2302 (Indoor)	GV-FE3402 (Indoor)	GV-FE5302 (Indoor)
			Without IR Ring		
					
Camera					
Image Sensor			1/2.5" progressive scan CMOS		
Picture Elements			1440 (H) x 1376 (V)		
Minimum Illumination	Color		0.15 Lux		
	B/W		0.10 Lux		
	IR ON		N/A		
Shutter Speed			Automatic, Manual (1/5 ~ 1/8000 sec.)		
White Balance			Auto, Manual (2800K ~ 8500K)		
Gain Control			Automatic		
S/N Ratio			45 dB		45 dB
WDR Pro (with WDR Sensor)			N/A		Yes
Dynamic Range			Up to 72 dB		Up to 100 dB
Operation					
Video Compression			H.264, MJPEG		
Video Streaming			Single Stream from H.264 or MJPEG		
Frame Rate			15 fps at 1440 x 1376 and 1280 x 1200	15 fps at 2048 x 1536, 1440 x 1376 and 1280 x 1200	10 fps at 2560 x 1920 15 fps at 2048 x 1944, 1440 x 1376 and 1280 x 1200
Audio Compression			G.711, AAC (optional)		
Sensor Input			N/A		
Alarm Output			N/A		
Optical Lens					
Megapixel			Yes		
Day/Night			Yes (with removable IR-cut filter)		
Focal Length			1.19 mm		1.32 mm
Maximum Aperture			F/2.0		F/2.0
Mount			M12, Pitch 0.5 mm		
Image Format			4.1 mm (image circle)		2.5"
Horizontal FOV			180°		
Operation	Focus		Fixed		
	Iris		Fixed		
	Zoom		Fixed		
Mechanical					
Temperature Detector			Yes		
Connectors	Power		Terminal block (2 pin), PoE		
	Ethernet		Ethernet (10/100 Base-T), RJ-45 Connector		
	Audio		1 In (built-in microphone) 1 Out (built-in speaker or stereo phone jack, 3.5 mm / 0.14")		
	Local Storage		Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported		
	Mini USB		GV-WiFi Adapter or USB hard drive		
General					
Environment Temperature			0 °C ~ 50 °C (32 °F ~ 122 °F)		
Humidity			10% to 90% (no condensation)		
Power Source			12V DC / 24V AC / PoE (IEEE 802.3af)		
Max. Power Consumption			8.6 W		
Regulatory			CE, FCC, RCM, RoHS compliant		
Dimensions	Camera Body	Hard-Ceiling Mount	Ø 160.25 x 48.36 mm (6.31 x 1.93")		
		In-Ceiling Mount	Ø 166.48 x 48.36 mm (6.55 x 1.93")		
Weight			410 g (0.9 lb)		
Vandal Resistance			IK10+ for metal casing		

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- Memory card slot (local storage) is not supported in Argentina.



Fisheye Camera Specifications (Part 4)



		GV-FE3403 (Indoor)	GV-FE5303 (Indoor)
		With IR Ring	
			
Camera			
Image Sensor		1/3.2" progressive scan CMOS	1/2.5" progressive scan CMOS
Picture Elements		2048 (H) x 1536 (V)	2560 (H) x 1920 (V)
Minimum Illumination	Color	0.08 Lux	0.15 Lux
	B/W	0.05 Lux	0.10 Lux
	IR ON	0 Lux	
Shutter Speed		Automatic, Manual (1/5 ~ 1/8000 sec.)	
White Balance		Auto, Manual (2800K ~ 8500K)	
Gain Control		Automatic	
S/N Ratio		47 dB	45 dB
WDR Pro (with WDR Sensor)		Yes	N/A
Dynamic Range		Up to 100 dB	Up to 72 dB
Video Compression			
Video Streaming		H.264, MJPEG	
Frame Rate		Single Stream from H.264 or MJPEG	
Audio Compression		15 fps at 2048 x 1536, 1440 x 1376 and 1280 x 1200	
Sensor Input		10 fps at 2560 x 1920; 15 fps at 2048 x 1944, 1440 x 1376 and 1280 x 1200	
Alarm Output		G.711, AAC (optional)	
Megapixel		N/A	
Day/Night		N/A	
Focal Length		1.19 mm	1.32 mm
Maximum Aperture		F/2.0	F/2.0
Mount		M12, Pitch 0.5 mm	
Image Format		4.1 mm (image circle)	2.5"
Horizontal FOV		180°	
Operation	Focus	Fixed	
	Iris	Fixed	
	Zoom	Fixed	
IR LED Quantity		6 IR LEDs	
Max. IR Distance		10 m (32.81 ft.)	
Temperature Detector			
Power		Yes	
Ethernet		Terminal block (2 pin), PoE	
Audio		Ethernet (10/100 Base-T), RJ-45 Connector	
Local Storage		1 In (built-in microphone)	
Mini USB		1 Out (built-in speaker or stereo phone jack, 3.5 mm / 0.14")	
Environment Temperature		Micro SD card slot (SD/SDHC, version 2.0 only, Class 10)	
Humidity		*SDXC and UHS-I card types are not supported	
Power Source		GV-WiFi Adapter or USB hard drive	
Max. Power Consumption		0 °C ~ 50 °C (32 °F ~ 122 °F)	
Regulatory		10% to 90% (no condensation)	
Dimensions		Camera: 12V DC / 24V AC / PoE (IEEE 802.3af)	
Weight		IR LED ring: 12V DC	
Vandal Resistance		PoE (IEEE 802.3 at)	
Note:		22 W	
1.		30 W	
2.		CE, FCC, RCM, RoHS compliant	
3.		Ø 175 x 48.36 mm (6.89" x 1.93")	
4.		870 g (1.92 lb)	
5.		1.045 kg (2.3 lb)	
6.		IK10+ for metal casing	

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- Memory card slot (local storage) is not supported in Argentina.



Fisheye Camera Specifications (Part 5)



		GV-FER3402 (Outdoor)	GV-FER5302 (Outdoor)
		Without IR Ring	
			
Camera			
Image Sensor		1/3.2" progressive scan CMOS	1/2.5" progressive scan CMOS
Picture Elements		2048 (H) x 1536 (V)	2560 (H) x 1920 (V)
Minimum Illumination	Color	0.08 Lux	0.15 Lux
	B/W	0.05 Lux	0.10 Lux
	IR ON	N/A	
Shutter Speed		Automatic, Manual (1/5 ~ 1/8000 sec.)	
White Balance		Auto, Manual (2800K ~ 8500K)	
Gain Control		Automatic	
S/N Ratio		47 dB	45 dB
WDR Pro (with WDR Sensor)		Yes	N/A
Dynamic Range		Up to 100 dB	Up to 72 dB
Operation			
Video Compression		H.264, MJPEG	
Video Streaming		Single Stream from H.264 or MJPEG	
Frame Rate		15 fps at 2048 x 1536, 1440 x 1376 and 1280 x 1200	10 fps at 2560 x 1920 15 fps at 2048 x 1944, 1440 x 1376 and 1280 x 1200
Audio Compression		G.711, AAC (optional)	
Sensor Input		N/A	
Alarm Output		N/A	
Optical Lens			
Megapixel		Yes	
Day/Night		Yes (with removable IR-cut filter)	
Focal Length		1.19 mm	1.32 mm
Maximum Aperture		F/2.0	F/2.0
Mount		M12, Pitch 0.5 mm	
Image Format		4.1 mm (image circle)	2.5"
Horizontal FOV		180°	
Operation	Focus		
	Iris	Fixed	
	Zoom		
IR LED Quantity		N/A	
Max. IR Distance		N/A	
Mechanical			
Temperature Detector		Yes	
Connectors	Power	Terminal block (2 pin), PoE	
	Ethernet	Ethernet (10/100 Base-T), RJ-45 Connector	
	Audio	1 In (built-in microphone), 1 Out (built-in speaker)	
	Local Storage	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported	
General			
Environment Temperature		-30°C ~ 50°C (-22°F ~ 122°F)	
Humidity		10% to 90% (no condensation)	
Power Source		12V DC / 24V AC / PoE (IEEE 802.3af)	
Max. Power Consumption		3.6 W	
Regulatory		CE, FCC, RCM, RoHS compliant	
Dimensions	Camera Body	Hard-Ceiling Mount	Ø 160.25 x 48.36 mm (6.31" x 1.93")
		In-Ceiling Mount	Ø 166.48 x 48.36 mm (6.55" x 1.93")
	Cable Length		1 m (3.28 ft.)
	Cable Diameter		Ø 6.2 mm (0.24")
	Max. Connector Diameter		Ø 30 mm (1.18")
Weight		500 g (1.1 lb)	
Ingress Protection		IP67	
Vandal Resistance		IK10+ for metal casing	

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- Memory card slot (local storage) is not supported in Argentina.



Fisheye Camera Specifications (Part 6)



		GV-FER3403 (Outdoor)	GV-FER5303 (Outdoor)
		With IR Ring	
			
Camera			
Image Sensor		1/3.2" progressive scan CMOS	1/2.5" progressive scan CMOS
Picture Elements		2048 (H) x 1536 (V)	2560 (H) x 1920 (V)
Minimum Illumination	Color	0.08 Lux	0.15 Lux
	B/W	0.05 Lux	0.10 Lux
	IR ON	0 Lux	
Shutter Speed		Automatic, Manual (1/5 ~ 1/8000 sec.)	
White Balance		Auto, Manual (2800K ~ 8500K)	
Gain Control		Automatic	
S/N Ratio		47 dB	45 dB
WDR Pro (with WDR Sensor)		Yes	N/A
Dynamic Range		Up to 100 dB	Up to 72 dB
Operation			
Video Compression		H.264, MJPEG	
Video Streaming		Single Stream from H.264 or MJPEG	
Frame Rate		15 fps at 2048 x 1536, 1440 x 1376 and 1280 x 1200	10 fps at 2560 x 1920 15 fps at 2048 x 1944, 1440 x 1376 and 1280 x 1200
Audio Compression		G.711, AAC (optional)	
Sensor Input		N/A	
Alarm Output		N/A	
Optical Lens			
Megapixel		Yes	
Day/Night		Yes (with removable IR-cut filter)	
Focal Length		1.19 mm	1.32 mm
Maximum Aperture		F/2.0	F/2.0
Mount		M12, Pitch 0.5 mm	
Image Format		4.1 mm (image circle)	2.5"
Horizontal FOV		180°	
Operation	Focus	Fixed	
	Iris	Fixed	
	Zoom	Fixed	
IR LED Quantity		6 IR LEDs	
Max. IR Distance		10 m (32.81 ft.)	
Mechanical			
Temperature Detector		Yes	
Connectors	Power	Terminal block (2 pin), PoE	
	Ethernet	Ethernet (10/100 Base-T), RJ-45 Connector	
	Audio	1 In (built-in microphone), 1 Out (built-in speaker)	
	Local Storage	Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported	
General			
Environment Temperature		-30°C ~ 50°C (-22°F ~ 122°F)	
Humidity		10% to 90% (no condensation)	
Power Source		Camera: 12V DC / 24V AC / PoE (IEEE 802.3af) IR LED ring: 12V DC	
Max. Power Consumption		22 W	
Regulatory		CE, FCC, RCM, RoHS compliant	
Dimensions	Camera Body	Hard-Ceiling Mount (with IR LED Ring) Ø 175 x 48.36 mm (6.89" x 1.93")	
	Cable Length	1 m (3.28 ft.)	
	Cable Diameter	Ø 6.2 mm (0.24")	
	Max. Connector Diameter	Ø 30 mm (1.18")	
Weight		960 g (2.12 lb)	
Ingress Protection		IP67	
Vandal Resistance		IK10+ for metal casing	

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- Memory card slot (local storage) is not supported in Argentina.



IP Speed Dome Camera Specifications (Part 1)





Camera		GV-SD010 (Indoor)			GV-SD010-S (Outdoor)		
		18X	23X	36X	18X	23X	36X
							
Image Sensor		1/4" Exview CCD	1/4" Progressive CCD	1/4" Exview CCD	1/4" Exview CCD	1/4" Progressive CCD	1/4" Exview CCD
Picture Elements		NTSC: 704 (H) x 480 (V) PAL: 704 (H) x 576 (V)					
Minimum Illumination		Color: 0.07 lux	0.1 lux	0.1 lux	0.07 lux	0.1 lux	0.1 lux
		B/W: 0.01 lux		0 lux		0.01 lux	
Shutter Speed		1 ~ 1/10000 sec	1/2 ~ 1/30000 sec	1 ~ 1/10000 sec	1 ~ 1/10000 sec	1/2 ~ 1/30000 sec	1 ~ 1/10000 sec
			1/1.5 ~ 1/30000 sec			1/1.5 ~ 1/30000 sec	
White Balance		Auto / Manual					
Gain Control		Auto / Manual					
S/N Ratio		> 50 dB (AGC Off)					
BLC		On / Off					
Optical Zoom		18X	23X	36X	18X	23X	36X
Digital Zoom		12X					
Video Compression		H.264, MPEG4, MJPEG					
Video Streaming		Stream 1 from H.264, MPEG4 or MJPEG Stream 2 from H.264, MPEG4 or MJPEG					
Frame Rate		30/25 fps (60/50 Hz) at 704 x 480 / 704 x 576					
Audio Compression		G.711, AAC (optional)					
Sensor Input		4					
Alarm Output		1					
Pan Travel		360° endless					
Tilt Travel		-10° ~ 190°					
Manual Speed		0.5° ~ 90°/s					
Presets		256					
Preset Accuracy		0.225°					
Preset Speed		5° ~ 400°/s					
Sequence		8					
Auto Pan		4					
Cruise		4					
Privacy Mask		24	8	24	24	8	24
Wide Dynamic Range		On / Off					
Dynamic Range		N/A					
Optical Lens							
Day/Night		Yes (with removable IR Cut Filter)					
Focal Length		4.1 ~ 73.8 mm					
Maximum Aperture		F1.4 to F3.0	F1.6 to F3.7	F1.6 to F4.5	F1.4 to F3.0	F1.6 to F3.7	F1.6 to F4.5
Operation (Focus/Zoom/Iris)		Auto/Manual					
Mechanical							
Connectors		3-pin terminal block					
		Ethernet (10/100 Base-T), RJ-45 connector					
		1 in 1 out (stereo jack, ø 35 mm)					
		4 in 1 out (I/O Wires)					
		BNC Connector (D1 Resolution)					
General							
Environment Temperature		0 °C ~ 40 °C (32 °F ~ 104 °F)			-45 °C ~ 50 °C (-49 °F ~ -122 °F)		
Humidity		20% to 90% (no condensation)					
Power Source		24V AC ± 10%, 1.5A			24V AC ± 10%, 3A		
Max. Power Consumption		20 W			65 W (with Heater)		
Regulatory		CE, FCC, RCM, RoHS compliant					
Dimensions		Camera Body: ø 131 x 226 mm (5.2" x 8.9")		Without sunshield: ø 172 x 302.5 mm (6.7" x 11.9") With sunshield: ø 190 x 302.5 mm (97.5" x 11.9")			
Weight		1.6 kg (3.5 lb)			With sunshield: 2.6 kg (5.7 lb)		
Ingress Protection		No			IP66		

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- Memory card slot (local storage) is not supported in Argentina.



IP Speed Dome Camera Specifications (Part 2)



Camera	GV-SD200 (Indoor)		GV-SD200-S (Outdoor)		GV-SD220 (Indoor)		GV-SD220-S (Outdoor)		
	18X		18X		20X / 30X		20X / 30X		
									
Image Sensor	1/2.8 Progressive Scan CMOS								
Picture Elements	1920 (H) x 1080 (V)				1920 (H) x 1080 (V)				
Minimum Illumination	Color	0.05 lux at F/1.6				0.05 lux at F/1.6			
	B/W	0.01 lux at F/1.6				0.005 lux at F/1.6			
Shutter Speed	1/30 ~ 1/10000 sec				1/1 ~ 1/10000 sec				
White Balance	Auto / Indoor / Outdoor / ATW / Manual				Auto / Manual				
Gain Control					Auto / Manual				
AGC Control					Auto / Manual				
S/N Ratio	N/A				> 50 dB (AGC Off)				
BLC					On / Off				
Optical Zoom	18X				20x / 30x				
Digital Zoom	10X				12x				
WDR Pro (with WDR sensor)					Yes				
Dynamic Range	N/A				Up to 100 dB				
Operation									
Video Compression	H.264, MJPEG								
Video Streaming	Dual Streams								
Frame Rate	30/25 fps (60/50 Hz) at 1920 x 1080				30/25 fps (60/50 Hz) at 1920 x 1080; 60/50 fps (60/50 Hz) at 1280 x 720				
Audio Compression	G.711				G.711, AAC (optional)				
Sensor Input					4				
Alarm Output	2				1				
Pan Travel	360° endless								
Tilt Travel	-10° ~ 190°				0° ~ 180°				
Proportional Pan & Tilt	On / Off (pan and tilt speed is proportional to the zoom ratio)								
Auto Flip	Digital / Mechanical / Off								
Movement Speed	0.5° ~ 90°/s (except Preset)				0.5° ~ 460°/s				
Presets	256				255				
Preset Accuracy	0.225°				0.2°				
Preset Speed	5° ~ 400°/s				0.5° ~ 460°/s				
Sequence					8				
Auto Pan	4				8				
Cruise	8				4				
Tour	16				8				
Privacy Mask	16				8				
Wide Dynamic Range	On / Off								
Calibration	Auto / Manual								
Optical Lens									
Megapixel	Yes								
Day/Night	Yes (with removable IR Cut Filter)								
Focal Length	4.7 ~ 84.6 mm				4.7 ~ 94.0 mm (20x); 4.3 ~ 129 mm (30x)				
Maximum Aperture	F/1.6								
Operation	Focus								
	Iris	Auto/Manual							
	Zoom								
Mechanical									
Temperature Detector	No				Yes				
Connectors	Power	3-pin terminal block, High power PoE(AT)		3-pin terminal block		DC Jack, PoE			
	Ethernet	Ethernet (10/100 Base-T), RJ-45 Connector							
	Audio	1 in 1 out (terminal block)				1 in 1 out (RCA female)			
	Digital I/O	4 in 2 out (12-pin terminal block)				4 in 1 out (I/O wires)			
	Local Storage	Micro SD card slot (SDHC for Class 6 card or above)				Micro SD card slot (SD/SDHC, version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported			
General									
Environment Temperature	0 °C ~ 40 °C (32 °F ~ 104 °F)		-40 °C ~ 50 °C (-40 °F ~ -122 °F)		-10 °C ~ 50 °C (14 °F ~ -122 °F)		-40 °C ~ 50 °C (-40 °F ~ -122 °F)		
Humidity	10% to 90% (no condensation)				20% to 90% (no condensation)				
Power Source	24V AC ± 10%, 1.5A / PoE		24V AC ± 10%, 3A		24V AC / 24V DC / PoE (IEEE 802.3at)		24V AC / 24V DC / PoE++ (60 W)		
Max. Power Consumption	20 W		65 W (with Heater)		30 W		60 W (with 30 W heater)		
Regulatory	CE, FCC, RCM, RoHS Compliant								
Dimensions	Camera Body	ø 171.7 x 228.71 mm (6.76" x 9")		With sunshield: ø 191.97 x 282.11 mm (7.55" x 11.1")		ø 172 x 221.9 mm (7" x 8.8")		ø 220 x 297.75 mm (8.7" x 11.7")	
Weight	1.62 kg (3.57 lb)		With sunshield: 2.32 kg (5.11 lb)		3.2 Kg (7.1 lb)		4.7 Kg (10.4 lb)		
Ingress Protection	-		IP66		-		IP67		
Vandal Resistance	-		-		-		IK10 for metal and polycarbonate casing		

Note:

- Product design and specifications are subject to change without notice.
- The frame rate and the performance may vary depending on the number of connections and data bitrates (different scenes).
- Memory card slot (local storage) is not supported in Argentina.
- GV-SD200/200-S only supports dual-streaming when stream 1 is set to H.264.
- GV-SD220/220-S starts supporting PoE from November, 2014.



IP Speed Dome Camera Specifications (Part 3)

		GV-SD2300 (Outdoor)	GV-SD2301 (Outdoor)
			
Camera			
Image Sensor		1/2.8 Progressive Scan CMOS	
Picture Elements		1920 (H) x 1080 (V)	
Minimum Illumination	Color	0.02 lux at F/1.6	
	B/W	0.01 lux at F/1.6	
Shutter Speed		1 ~ 1/10000 sec	
White Balance		Auto / Manual	
Gain Control		Auto / Manual	
S/N Ratio		50 dB (AGC Off)	
BLC		On / Off	
Optical Zoom		20x	
Digital Zoom		12X	
Video Compression		H.264, MJPEG	
Video Streaming		Dual streams from H.264 or MJPEG	
Frame Rate		30/25 fps (60/50 Hz) at 1920 x 1080 60/50 fps (60/50 Hz) at 1280 x 720	
Audio Compression		G.711, AAC (optional)	
Sensor Input		4 Input (Dry Contact)	
Alarm Output		1 Digital Output (200mA 5V DC)	
Pan Travel		360° endless	
Tilt Travel		0° ~ 180°	-20° ~ 200°
Manual Speed		0.5° ~ 460/s	
Presets		255	
Preset Accuracy		0.2°	
Preset Speed		0.5° ~ 460/s	
Sequence	Max Number	8	
	Max Presets Allowed	16	
Auto Pan		8	
Cruise		4	
Privacy Mask		8	
Wide Dynamic Range		On / Off	
Dynamic Range		Up to 72dB	
Optical Lens			
Day/Night		Yes (with removable IR Cut Filter)	
Focal Length		4.7 ~ 94 mm	
Maximum Aperture		F / 1.6	
Operation	Focus	Auto/Manual	
	Zoom	20x	
	Iris	Auto/Manual	
Mechanical			
Connectors	Power	DC Jack, PoE	
	Ethernet	10/100 Base-T, RJ-45 connector	
	Audio	1 in (RCA female for microphone)	
		1 out (RCA female for speaker)	
	Digital I/O	I/O Wires	
Local Storage	Micro SD card slot (SD/SDHC, SD version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported	SD card slot (SD/SDHC, SD version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported	
General			
Environment Temperature		-40 °C ~ 50 °C (-40 °F ~ 122 °F)	-40 °C ~ 70 °C (-40 °F ~ 158 °F)
Humidity		20% to 90% (non-condensing)	
Power Source		24V AC ± 10%, 3A / 24V DC ± 10%, 3.75A / High PoE (PoE++)	
Max. Power Consumption		60 W (with 30 W Heater)	50 W (with 30 W Heater)
Regulatory		CE, FCC, RCM, RoHS compliant	
Dimensions	Camera Body	Ø 220 x 297.75 mm (8.66" x 11.72")	Ø 212 x 215 mm (8.35" x 8.46")
Weight (With rack)		4.7 kg (10.4 lb)	2.9 kg (6.4 lb)
Ingress Protection		IP67	
Vandal Resistance		IK10 for metal and polycarbonate casting	

Note:

1. The frame rate and performance may vary depending on the number of connections and data bitrates (different scenes).
2. SDXC and UHS-I card types are not supported.
3. No memory card slot (local storage function) is not supported in Argentina.