







Comparison Chart for GV-IP LPR Cameras

		GV-LPC1100	GV-IP LPR Camera 5R
			
Capturing License Plates		Yes	
Recognizing Plate Numbers		N/A	
Camera (only for reflective license plates)			
Image Sensor		1/3" B/W progressive scan CMOS	
Picture Elements		1280 (H) x 1024 (V)	
Camera Type		B/W	
Shutter Speed		Automatic, Manual (1/500 ~ 1/8000 sec)	
White Balance		Auto / Manual (2800K ~ 8500K)	
Max. Speed		120 km/h (75 mph)	60 km/h (37 mph)
Operation			
Video Compression		H.264, MJPEG	
Video Streaming		Dual streams	
Frame Rate		30 fps at 1280 x 1024	
Audio Compression		G. 711, AAC (optional)	N/A
Optical Lens			
Megapixel		Yes	
Lens Type		Motorized Varifocal Lens	
Focal Length		9 ~ 22 mm	3 ~ 9 mm
Maximum Aperture		F/1.2"	
Mount		Ø14 mm	
Image Format		1/2.7"	
Operation	Focus	Auto Focus	
	Zoom	3x Optical Zoom	
	Iris	P-Iris	DC drive
IR LED Quantity		4	12
Optimal IR Distance		10 m (32.81 ft)	5 m (16.4 ft)
Suggested Range of IR Distance		8 ~ 10 m (26.2 ~ 32.8 ft)	3 ~ 5 m (9.84 ~ 16.4 ft)
Mechanical			
Temperature Detector		Yes	
Connectors	Power	DC 48V 2.5A, High PoE (PoE++, 120 W)	PoE+ (IEEE 802.3at)
	Ethernet	Ethernet (10/100 Base-T), RJ-45 connector	
	Audio	1 In (external microphone) 1 Out (Stereo phone jack, 3.5 mm / 0.14")	N/A
	Digital I/O	1 in / 1 out	N/A
	TV-Out	BNC connector (640 x 480 resolution)	N/A
LED Indicator		N/A	
General			
Environment Temperature		-40°C ~ 50°C (-40°F ~ 122°F)	-20°C ~ 50°C (-4°F ~ 122°F)
Humidity		10% to 90% (no condensation)	
Power Source		DC 48V 2.5A, High PoE (PoE++, 120 W)	PoE+ (IEEE 802.3at)
Max. Power Consumption		50 W	16.6 W
Regulatory		CE, FCC, C-Tick and RoHS compliant	
Dimensions (L X W X H)		406 x 145 x 109 mm (16" x 5.7" x 4.3") (without support rack)	289.02 x 87.75 x 148.95 mm (11.4" x 3.45" x 5.86")
Weight		With support rack: 3.32 kg (7.32 lb) Without support rack: 2.62 kg (5.78 lb)	1.4 kg (3.08 lb)
Ingress Protection		IP67	
Vandal Resistance		IK10 for metal casing	
Heater On		-40°C ~ 8°C (-40°F ~ 46.4°F)	N/A
Fan		Constantly On	




All specifications are subject to change without notice.



		GV-LPR1200	GV-LPC1200
			
Capturing License Plates		Yes	
Recognizing Plate Numbers		Yes (Built-in LPR processor)	N/A
Camera (only for reflective license plates)			
Image Sensor		Megapixel B/W progressive scan CCD	
Picture Elements		1280 (H) x 720 (V)	
Camera Type		B/W	
Shutter Speed		Automatic: 1/1000 ~ 1/10000 sec Manual: 1/250 ~ 1/2000 sec	
S/N Ratio		52 dB	
Max. Speed		200 km/h (124.27 mph)	
Operation			
Video Compression		H.264, MJPEG	
Video Streaming		Dual streams from H.264 and MJPEG	
Frame Rate		30 fps at 1280 x 720	
Audio Compression		G.711, AAC (Optional)	
Optical Lens			
Megapixel		1 MP	
Lens Type		Motorized varifocal lens	
Focal Length		4.7 mm ~ 47 mm	
Maximum Aperture		F/3.5"	
Image Format		1/3"	
Operation	Focus	Auto	
	Zoom	10X optical zoom	
	Iris	Auto Focus	
IR LED Quantity		8 high power IR LEDs	
IR Distance		10 ~ 20 m (32.8 ~ 65.6 ft)	
Mechanical			
Temperature Detector		Yes	
Connectors	Power	DC 12V	
	Ethernet	RJ-45	
	Audio	1 In (microphone jack, 3.5 mm / 0.14") 1 Out (stereo phone jack, 3.5 mm / 0.14")	
	Digital I/O	2 In / 2 Out	
	RS-485	RS-485+ / RS-485- (for recognition data output)	N/A
	Local Storage	Micro SD card slot (SD/SDHC, SD version 2.0 only, Class 10) * SDXC and UHS-I card types are not supported.	N/A
	TV-Out	BNC connector (640 x 480 resolution)	
	Mini USB	Mini USB port on the circuit board (for UMTS)	
LED Indicator		N/A	
General			
Environment Temperature		-40°C ~ 50°C (-40°F ~ 122°F)	
Humidity		10% to 90% (no condensation)	
Power Source		DC 12V, 5A	
Max. Power Consumption		54 W	
Regulatory		CE, FCC, RCM, RoHS compliant	
Dimensions (L X W X H)		406 x 145 x 109 mm (16" x 5.7" x 4.3") (Without support rack)	
Weight		With support rack: 3.32 kg (7.32 lb)	
		Without support rack: 2.62 kg (5.78 lb)	
Ingress Protection		IP67	
Vandal Resistance		IK10 for metal casing	
Heater On		-40°C ~ 5°C (-40°F ~ 41°F)	
Fan		Constantly On	

All specifications are subject to change without notice.



		GV-LPC2210	GV-LPC2211	GV-LPC2011
				
Capturing License Plates		Yes		
Recognizing Plate Numbers		N/A		
Camera (only for reflective license plates)				
Image Sensor		1/2.8" progressive super low lux CMOS		
Picture Elements		1920 (H) x 1080 (V)		
Camera Type		Color, B/W		
Shutter Speed		Auto, Manual (1/120 ~ 1/2000 sec)		
White Balance		Auto / Manual (2800K ~ 8500K)		
S/N Ratio		52 dB		56 dB
Max. Speed		120 km/h (75 mph)		60 km/h (37 mph)
Operation				
Video Compression		H.264, MJPEG		
Video Streaming		Dual streams from H.264 or MJPEG		
Frame Rate		30 fps at 1920 x 1080		
Audio Compression		G. 711, AAC (optional)		N/A
Optical Lens				
Megapixel		2 MP		
Lens Type		Motorized Varifocal Lens		
Focal Length		9 ~ 22 mm		3 ~ 9 mm
Maximum Aperture		F/1.2"	F/2.0 ~ F/3.5	F/1.7
Mount		Ø 14 mm		
Image Format		1/2.7"		
Operation	Focus	Auto Focus		Remote Focus
	Zoom	2.5x optical zoom		3x optical zoom
	Iris	P-Iris		
IR LED Quantity		4 high power IR LEDs		24 IR LEDs
IR Distance		10 ~ 20 m (32.8 ~ 65.6 ft)		5 ~ 9 m (16.4 ~ 29.6 ft)
Mechanical				
Temperature Detector		Yes		
Connectors	Power	DC 48V, High PoE (PoE++, 120 W)		DC 12V, PoE (IEEE 802.3af)
	Ethernet	RJ-45		
	Audio	1 In (microphone jack, 3.5 mm / 0.14"); 1 Out (stereo phone jack, 3.5 mm / 0.14")		N/A
	Digital I/O	1 In / 1 Out		
	TV-Out	BNC connector (640 x 480 resolution)		
General				
Environment Temperature	Start-up	-40°C ~ 50°C (-40°F ~ 122°F)	-20°C ~ 50°C (-4°F ~ 122°F)	-20°C ~ 50°C (-4°F ~ 122°F)
	Operation		-30°C ~ 50°C (-22°F ~ 122°F)	-30°C ~ 50°C (-22°F ~ 122°F)
Humidity		10% to 90% (no condensation)		
Power Source		DC 48V 2.5A, High PoE (PoE++, 120 W)		DC 12V, PoE (IEEE 802.3af)
Max. Power Consumption		50 W		12.3 W
Regulatory		CE, FCC, RCM, RoHS compliant		
Dimensions (L X W X H)		406 x 145 x 109 mm (16" x 5.7" x 4.3") (without support rack)	142.14 x 77.72 x 102.75 mm (5.6" x 3.06" x 4.05")	
Weight		With support rack: 3.32 kg (7.32 lb) Without support rack: 2.62 kg (5.78 lb)	810 g (1.8 lb)	
Ingress Protection		IP67		
Vandal Resistance		IK10 for metal casing		
Heater On		-40°C ~ 8°C (-40°F ~ 46.4°F)		N/A
Fan		Constantly On		

- All specifications are subject to change without notice.